NEW MEXICO OIL CONSERVATION COMM.SION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate	e nature of report	By checking below		
PORT ON BEGINNING DRILLING OPERATION	L # -	EPORT ON REPAIR		<u>-</u> -
PORT ON PESULT OF SHOOTING OR CHE	MICAL X	REPORT ON PULLIN ALTERING CASIN	G OR OTHERWISE	•
PORT ON RESULT OF TEST OF CASING SHUT-OFF	F	REPORT ON DEEPEN	VING WELL	X
PORT ON RESULT OF PLUGGING OF WEL	.L			
Art	esia. New Me	exico Place	November	15, 1948
L CONSERVATION COMMISSION, inta Fe, New Mexico	·	1.460		
				of the
entlemen: ollowing is a report on the work done a	and the results obta	ained under the he	eading noted above	at the
Vencey-Herris Company	Etz-State	(Humble)	Well No.	in the
Company of Operator W NE SE of Sec.	16 _T	178	, R. 30E	, N. M. P. M.,
*	10.	ady .		County
he dates of this work were as follows:		10 10h0	A. Maramhe	m 14 1948.
otice of intention to do the work was (not approval of the proposed plan was (not be proposed pl	NT OF WORK	DONE AND RES	SULTS OBTAIN Sacks. Di	ED rilled to to th 200 gall
otice of intention to do the work was (not approval of the proposed plan was (not be proposed pl	nt of Work I and cement Plugged b 000 gallons; Plugged bs ny depth.	cone and Resided with 100 back to 3386 bridge back to 3235	sults OBTAIN sacks. Di , washed wi k to 33005 and treate	rilled to to th 200 gall and treated d w/6000 gal
DETAILED ACCOU Set 5 1/2" O.D. at 3104" depth 3413' (SLM-3417'). acid and treated with 10 with 4000 gallons acid. No cil encountered at an	nt of Work I and cement Plugged b 000 gallons; Plugged bs ny depth.	DONE AND RES	sults OBTAIN sacks. Di , washed wi k to 33005 and treate	rilled to to th 200 galle and treated
Notice of intention to do the work was (and approval of the proposed plan was (and approval of t	and cement Plugged b OOO gallons; Plugged ba ny depth. Yancey-	ed with 100 each to 3386 bridge back to 3235 -Harris Comp	sults OBTAIN Sacks. Dr No. washed with the sack to 3300's and treated pany Superinter Superinter	rilled to to the state of the 200 galle and treated dw/6000 gal. erintendent Title the information give ondent
Notice of intention to do the work was (not approval of the proposed plan was (not be proposed p	and cement Plugged b OOO gallons; Plugged ba ny depth. Yancey-	ed with 100 ack to 3386 bridge back to 3235 -Harris Company I hereby swe above is true	sacks. Dr. Sacks.	rilled to to the state of the 200 galle and treated dw/6000 galle erintendent Title the information give endent arris Company

Title