

RECEIVED B

MAY 10 1984

O. C. D.

ARTESIA, OFFICE

LC064988A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR

Damson Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Box 50460, Midland, Texas 79710

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1,650' FNL & 1,650' FWL of Sec.

AT TOP PROD. INTERVAL: Same

AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Berry Federal "A"

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 21, T-17-S, R-30-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. API NO.

NA

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3650 GL Cable tooled hole

(NOTE: Report results of multiple completion or zone change on Form 9-330)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give surface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9/30/83 RU Service Unit and fishing tools.

9/31-10/13/83 Millover and recovered fish. Fish was tubing, seating nipple and a mud anchor.

10/14/83 RU Service Company and acidized OH 2,584'-3,400' w/2000 gallons 15% HCL acid with 5% Pentafax.

10/15/83 TIH with tubing, rods and pump. Prepare to return to production.

10/16-25/83 Waiting on electric service.

10/26/83 Pumped 18B0/91/BW in 24 hrs.

12/20/83 Pumped 2B0/10BW in 24 hrs.

Production before work 0/0 as well was TA'ed.

Subsurface Safety Valve: Manu. and Type NA Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED C. M. Bloodworth TITLE District Engineer DATE 12/20/83

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY SWQ TITLE DATE

CONDITIONS OF APPROVAL IF ANY:

MAY 8 1984

Carlsbad

NEW MEXICO

\*See Instructions on Reverse Side