

Copy 2 of 1

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE MANNER INDICATED*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC 029020 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ P & A

2. NAME OF OPERATOR

Atlantic Richfield Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

2310' FSL & 990' FWL (Unit letter 'L')

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Dale H. Parke "B" Tr. A

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Jackson - Abo

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 23, T17S, R30E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well has been plugged and abandoned in the following manner. Loaded hole w/gel mud. Set 4½" 11.6# Titan CIBP @6810', capped w/3 sx cement (37'). Spotted 20 sk cement plug 2356-2125'. Placed 10 sk cement plug in top of well and erected dry hole marker. Job complete 6/5/72. 8-5/8" and 4½" casing strings remain intact. Gel mud was used to spot all cement plugs. All gel mud contained 25 sx gel/100 barrels of water.

18. I hereby certify that the foregoing is true and correct

SIGNED

J. L. Knott

TITLE

Dist. Drlg. Supervisor

DATE

6/7/72

(This space for Federal or State office use)

APPROVED BY
COMMISSIONER OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
MAR 26 1974
MAR 26 1974
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side