Form 9-331 Dec. 1973

PULL OR ALTER CASING MULTIPLE COMPLETE

ABANDON \* Permanently

CHANGE ZONES

(other)

Drawer DD Artesia, NM

88210

5. LEASE

JU SFP 20 1982 3

OIL & GAS U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

Form Approved.

Budget Bureau No. 42 GEVED

## UNITED STATES

## DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Unsuccessf#1

	LC-030570	(b)	SED on	100
6	IF INDIAN ALLOTTEE O	RTRIB	F NAME &	1306

deocodione conver	* * * * * *		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREFMENT NAME Grayburg Jackson Unit RIESIA, OFFICE		
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Tract 13		
well well other Water Injection Well  2. NAME OF OPERATOR	9. WELL NO. 8		
General Operating Company  3. ADDRESS OF OPERATOR Suite 1007 Riglea Bank Bldg	10. FIELD OR WILDCAT NAME Grayburg Jackson Queen SA		
Fort Worth, Texas 76116	11. SEC., T., R., M., OR BLK. AND SURVEY OR		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Section 25-T17S-R30E, NMPM		
AT SURFACE: 660' FSL & 1980' FWL AT TOP PROD. INTERVAL: Section 25-T17S-R30E	12. COUNTY OR PARISH 13. STATE Eddy New Mexico		
AT TOTAL DEPTH:  16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO. Not Available		
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDR AND WD) 3552 GR		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:			
TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone		

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Work was commenced on Sept. 13, 1982 to temporarily abandon this inactive water injection well as approved by the MMS on August 10, 1982.

After cleaning out inside of the 3-1/2" OD casing in the well to a depth of 3235', efforts on Sept. 16, 1982 to run a bridge plug to a depth of 3200' were unsuccessful due to the roughness of the casing.

On September 16, 1982, we proposed and obtained verbal approval from Mr. Armando Lopez to permanently plug this well by pumping cement down the 3-1/2" OD casing into the casing perforations from 3300' - 38' and leaving the inside of the 3-1/2" OD casing cemented to the surface.

This work is schedule	ed for September 17, 1982	. The appropriate authorities
with the Energy and Minera	ls Department, 0il & Gas	Division have been notified
of this proposed work.		Posted FO-2 Posted FO-2 Temp. Ft.
Subsurface Safety Valve: Manu. and Type _		
18. I hereby certify that the foregoing is true signed C. W. Stumhoffer	Vice President	
	(This space for Federal or State office use)	
APPROVED BY	TITLE	DATE
CONDITIONS OF APPROVAL, IF ANY:		APPROVED
	*See Instru. tions on Reverse Side	SEP 2 1 1982