

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY  
AUG 11 1982  
O. C. D.

ARTESIA, OFFICE  
SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other Water Injection Well

2. NAME OF OPERATOR

General Operating Company ✓

3. ADDRESS OF OPERATOR Suite 1007 Ridglea Bank Bldg.  
Fort Worth, Texas 76116

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 660' FEL  
AT TOP PROD. INTERVAL: Section 27-T17S-R30E  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☒ T.A.  
(other)

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐

5. LEASE

LC-059376

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Grayburg Jackson Unit

8. FARM OR LEASE NAME

Tract 11

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Grayburg Jackson Queen SA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 27-T17S-R30E, NMPM

12. COUNTY OR PARISH | 13. STATE

Eddy New Mexico

14. API NO.

Not Available

15. ELEVATIONS (SHOW DF, KDR AND WD)  
3630' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

To comply with New Mexico Oil Conservation Division Rule 705-A, we propose to temporarily abandon Grayburg Jackson Unit Tract 11 Well No. 1 as a water injection well as follows:

- (1) Set cast iron bridge plug in 4½" OD casing at an approximate depth of 3100' to plug off perforations from 3198'-3206'.
- (2) Pressure test 4½" OD casing above bridge plug to 500 psi.
- (3) Shut in well with casing loaded with inhibited fresh water.

This work is being scheduled for the week of August 2, 1982.

Subsurface Safety Valve: Manu. and Type None Set @        Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED C. W. Stumhoffer TITLE Vice President DATE July 27, 1982  
C. W. Stumhoffer

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

APPROVED

TITLE

DATE

AUG 10 1982  
JAMES A. GILLHAM  
DISTRICT SUPERVISOR

\*See Instructions on Reverse Side

RECEIVED  
JUL 29 1982

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO