

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on re-
verse side)

Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back at a different location.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Phillips Petroleum Company

3. ADDRESS OF OPERATOR

4001 Penbrook Street, Odessa, Texas 79702

4. LOCATION OF WELL (Report location clearly and in accordance with all State requirements.)
See also space 17 below.)
At surface

Unit L, 1946' FSL & 662' FWL

14. PERMIT NO.

API No. 30-015-04387

15. ELEVATIONS (Show whether on, or below, surface)

3599' GR

5. LEASE DESIGNATION AND SERIAL NO.

LC-028793-C

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Burch C Fed

9. WELL NO.

39

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson-SR-Q-Gb/SA

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

30, 17-S, 30-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PCCL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Commencement of Plugback

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

2-04-87: 7953' PTD. MI & RU WSU. Cleaned out cellar, cut off casing stub, installed 8-5/8" Huber head & BOP.

2-05 thru

2-08-87: Drld out to 7012'. Spotted 60 sx of Class "C" cmt at 6964'-6800', 6211'-6050' and 3769'-3600'. Circ 20 sx of cmt to surface. Ran 87 jts of 5-1/2" 17#, K-55 ST&C casing, set at 3611'. Cmt'd with 300 sx TLW, 10#/sx salt, 10% Diacel D, followed with 600 sx Class "C", 2% CaCl₂. Displaced with 23 bbls 10% Acetic acid, 50 bbls 2% KCL FW. Circ 51 sx cmt. WOC 40 hrs.

2-09-87: Ran GR-CCL from PBTD 3566' to surface. Perf'd 5-1/2" casing w/4" OD casing gun 2662'-3425' (total of 94' - 188 holes).

2-10 &

2-11-87: Acidized perfs 3048'-3425' with 3200 gals 15% NEFE HCL acid. Swbd 9 hrs, 40 BW.

2-12-87: Swb'g to recover load water.

Note: As of 3-16-87: Still prep'g to recover load.

18. I hereby certify that the foregoing is true and correct

SIGNED

W. J. Mueller

TITLE

Engr. Supvr. Reserv.

DATE 2-13-87

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

FEB 18 1987

ACCEPTED FOR RECORD

FEB 17 1987

Jm

P.B.R. Regulatory Section

*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO