

UNITED STATES  
DEPARTMENT OF THE INTERIORS  
GEOLOGICAL SURVEY

MINERALS COMMISSION  
Drawer DD  
Artesia, NM 88210

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other Water Injection
2. NAME OF OPERATOR  
General American Oil Company of Texas
3. ADDRESS OF OPERATOR  
P. O. Box 128 Loco Hills, New Mexico 88255
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2310' FSL and 2232' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

- ☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE  
LC-060529
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME  
RECEIVED
8. FARM OR LEASE NAME  
Beeson F
9. WELL NO.  
#13
10. FIELD OR WILDCAT NAME  
Loco Hills
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 31, T-17-S, R-30-E
12. COUNTY OR PARISH  
Eddy
13. STATE  
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3562' DF

(NOTE: Do not use for multiple completions or zone changes on Form 9-330.)

RECEIVED

DEC 10 1982

OIL & GAS

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give pertinent dates, measured and true vertical depths for all markers and zones pertinent to this work.)

This well was plugged and abandoned as follows:

1. A cement plug was set from 2825'-2715' to cover open hole section 2825'-2725'.
  2. Perforated 4 holes @ 1260', top of Yates, and squeezed 55 sacks of cement into formation. Tagged plug @ 1158'.
  3. Perforated 4 holes @ 495', top of salt, and squeezed 55 sacks of cement into formation. Tagged plug @ 385'.
  4. Perforated 4 holes @ 385' and squeezed 55 sacks of cement into formation. Tagged plug @ 310'.
  5. Rigged up 7" swedge on casing and squeezed 55 sacks of cement. Tagged plug @ 50'.
  6. 10 sack plug was set at surface.
  7. Permanent well marker was erected November 20, 1982.
  8. Location, road was cleaned, ripped and re-seeded.
- Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Randall N. Hawkins TITLE Field Supt. DATE December 8, 1982

APPROVED (This space for Federal or State office use)  
(Orig. Sgd) PETER W. CHESTER  
APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

MAR 9 1983  
FOR  
JAMES A. GILLHAM  
DISTRICT SUPERVISOR

\*See Instructions on Reverse Side

Posted 10-14-83  
p2 a