

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP (Other instruction
verse side)

Budget Bureau No. 1004-0135
Expires August 31, 1985

45F

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

RECEIVED

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER ☒ WIW

2. NAME OF OPERATOR
Hondo Oil & Gas Company

3. ADDRESS OF OPERATOR
P. O. Box 2208, Roswell, NM 88202

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1980' FSL & 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3968' GR

OCT 17 '89

O. C. D.
ARTESIA OFFICE

5. LEASE DESIGNATION AND SERIAL NO.
LC-029426-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
H. E. West "B"

9. WELL NO.
26

10. FIELD AND POOL, OR WILDCAT
Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND SURVEY OR ARMA
Sec. 3-T17S-R31E

12. COUNTY OR PARISH
Eddy

13. STATE
NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) deepened and ran pkr. & tbq.

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

9/1-14/89 Drilled out well to old TD of 3757' and deepened with 3 7/8" bit to new TD of 3941'.

9/21/89 Acidized OH 3757-3950' with 1500 gal. 15% NEFE acid. Reacidized OH 3757-3950' with 6000 gal. SXE diesel emulsion + 1840# of rock salt. Flowed and swabbed well back.

9/22/89 Perforated 3401-3744' with 41 shots. Acidized 3401-3744' with 8000 gal. 15% NEFE acid.

9/25/89 Ran in hole with Guiberson ER-6 packer and 107 jts. 2 3/8" plastic-coated tubing and set @ 3307'. Well ready for injection. (Tested to 350 psi for 15 min. - held okay.)

OCT 6 11 12 AM '89

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED Lisa Bohannon

TITLE Engineering Technician

DATE 10/4/89

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD
DATE

OCT 12 1989

*See Instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO