Form 3160-5 (June 1990)

Conditions of approval, if any:

UNITED STATES DEPARTME! | JF THE INTERIOR

BUREAU OF LAND MANAGEMENT FORM APPROVED Budget Bureau No. 1004-0135 Expires March 31, 1993 SUNDRY NOTICES AND REPORTS ON WELLS Lease Designation and Serial No. Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. 6. If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT—" for such proposals SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ☐ Gas Well ☑ Other P&A'd Well Name and No. 2. Name of Operator **DEVON ENERGY CORPORATION (NEVADA)** H. E. West "B" #5 3. Address and Telephone No. 9. API Well No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611 30-015-05069 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 1980' FNL & 1980' FWL, Sec. 4-17S-31E Grayburg Jackson JUN 97 1397 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION ☐ Notice of Intent Change of Plans Recompletion **New Construction** Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection ☐ Dispose Water Other e: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 5/6/96 to 5/17/96 - Attempted to clean out to convert to water injection well. Encountered at tight spot @ 3468'. The well was plugged and abandoned as follows: 6/9/97 - TIH w/bit to 3100'. 6/10/97 - Set cmt retainer @ 3070' & squeezed 4 1/2" liner w/75 sxs Class "C" cmt. Left 50' cmt on top of retainer. Perf'd 4 holes @ 1670'. Set cmt retainer @ 1614' & squeezed off salt section w/100 sxs Class "C" cmt. Left 50' cement on top of retainer. 6/11/97 - Perf'd 4 holes @ 732'. Pumped 225 sxs Class "C" cmt. Displaced cmt to 632', 100' above perfs. 6/12/97 - Spotted a cmt plug 50'-surface. Installed dry hole marker. Status: Plugged & abandoned. 14. I hereby certify that the foregoing is true and correct Karen Byers Title Engineering Technician (ORIG. SGD.) DAVID K. GLAM JUN 23 1997 Approved by

> Approved as to plugging of the well bore. Liability under bend is retained until

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representation to any matter within its jurisdiction.