Form 3160-5 (June 1990)

UNITED STATES DEPARTMF "OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. Oil Division APPROVED

Budget Bureau No. 1004-0135

Evnires March 31, 1993

8	1	1	S.	1	st	St	reet
v			~ .	·	v		

SUNDRY NOTICES AND REP Do not use this form for proposals to drill or to deepe Use "APPLICATION FOR PERMI	n or reentry to a different re	ia, NM 882 1 0=283 ination and Serial No. LC-029435-B 6. If Indian, Allottee or Tribe Name						
SUBMIT IN TRIPL	ICATE							
1. Type of Well Oil Well Gas Well Other WIW		7. If Unit or CA, Agreement Designation						
2. Name of Operator DEVON ENERGY CORPORATION (NEVADA)		8. Well Name and No.						
3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA C	CITY, OKLAHOMA 73102 (405) 2	J. L. Keel "B" #13 9. API Well No.						
4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 660' FSL & 1980' FEL of Section 5-T17S-R31E		30-015-05078 10. Field and Pool, or Exploratory Area Grayburg Jackson Field 11. County or Parish, State						
		Eddy County, NM						
CHECK APPROPRIATE BOX(s) TO IND	ICATE NATURE OF NO	TICE, REPORT, OR OTHER DATA						
TYPE OF SUBMISSION	TYPE OF ACTION							
Notice of Intent✓ Subsequent Report	Abandonment Recompletion Plugging Back	Change of Plans New Construction Non-Routine Fracturing						
Final Abandonment Notice	Casing Repair Altering Casing Other	Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well						
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, subsurface locations and measured and true vertical depths for all markers at Workover existing water injection well as follow/28/00 – MIRU pulling unit. Run bit and so	OWS:							
08/29/00 - Set CIBP @ 2960', tested CIBP to 1000psi. Plug tested good.								
09/28/00 - Run and cement a string of 5" 15# casing from top of existing 5" liner to surface. Cemented casing with 205 sxs Class "C" + 2% Cacl. Circulated cement to surface. WOC.								
10/02/00 - Drilled out float collar and guide shoe to 2952'. Circulate wellbore clean.								
10/03/00 – Drill out cement and CIBP. Circulate wellbore clean. Flow well to pit.								
10/10/00 - RIH with packer, seat nipple and								
14. I hereby certify that the foregoing is true and correct								
Signed Charles Hartton	Charles H. Carleton Title Sr. Engineering Tech.	Date October 11, 2000						
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title	Date						