Form 3160-5 (June 1990)

	Print the fact of the		WCCE, 729		
form 3160-5 func 1990) Do not use this fo	DEPARTMEN BUREAU OF I SUNDRY NOTICES orm for proposals to dri	TED STATES T OF THE INTERIOR AND MANAGEMENT AND REPORTS ON WELLS If or to deepen or reentry to a R PERMIT—" for such propose	different reservoir.	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No. #LC-029426-B 6. If Indian, Allottea or Tribe Name	
SUBMIT IN TRIPLICATE				7. If Unit or CA, Agreement Designation	
1 Type of Well Oil Gas Well Well Woller WIW 2 Name of Operator SOCORRO PETROLEUM COMPANY 3 Address and Telephone No. P.O. BOX 38, LOCO HILLS, N.M. (505) 677-3223 4 Location of Well (Footage, Sec., T., R., M., or Survey Description) 660! FNL & 1980! FWL , Sec 10-T17S-R31E				8. Well Name and No. H, E, WEST "B" # 19 9. API Well No. 30-015-05125 10. Field and Pool, or Exploratory Area GRAYBURG JACKSON 11. County or Parish, State EDDY CO., N.M.	
12 CHECK	APPROPRIATE BOX(3) TO INDICATE NATURE O	F NOTICE, REPOR	T, OR OTHER DATA	
TYPE OF	SUBMISSION	TYPE OF ACTION			
	of Iment ent Report bandonment Notice	Abandonment Recompletion Plugging Back Casing Repair Attering Casing KKother <u>Clean</u> Acidi		Change of Plans New Construction Non-Routine Practuring Water Shut-Off Conversion to Enjection Dispose Water (Note: Report results of multiple geosphetion on Well Completion or Recompletion Report and Log form 1	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1.) Dig small working pit. Bleed well down. Haul excess wtr. Catch wtr samples & analyze for solids, hydrocarbons & bacteria.
- 2.) Release pkr. POH w/tbg & pkr.
- 3.) RIH w/tbg & bit or bailer.
- 4.) Clean out well to TD.
- 5.) Run cased hole logs.
- 6.) Acidize well to clean perfs & remove any near well bore damage. Flow & swab back acid residue. Drain and back fill working pit.

7.) RIH w/plastic coated the & pkr. Set pkr no more than ± 50' above top pers. WEAU Of Place one drum of corrosion inhibitor in casing annulus & pressure test. Hust hold 300f for 30 minutes. hold 300# for 30 minutes.

8.) Place well on injection & establish injection rate.

Production Manager PETROLEUM ENGINEER ୍ତ ।993

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements