

Form 1-531
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Copy to SL

Form approved
Budget Bureau No. 42-R1424

5. LEASE DESIGNATION AND SERIAL NO.

LC 029426 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

H.E. West "B"

9. WELL NO.

21

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10, T-17S, R-31E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Atlantic Richfield Company

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL, 660' FWL (Unit Letter M)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3889' Grd.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☒

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

To prepare this well for expected waterflood response, we propose the following work:

Add these perforations w/one JS at each depth: 3416, 3417, 3418, 3451, 3453, 3455, 3457, 3482, 3484, 3490, 3492, 3496, 3498, 3502, 3563, 3567, 3577, 3581, 3636, 3640, 3642, 3644, 3646, 3700, 3736, 3738, 3774 & 3775'. Treat these perforations w/1500 gallons 15% HCl acid and ball sealers and frac w/40,000 gallons of slick water containing 40,000# of 20/40 sand.

RECEIVED
MAY 25 1970
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

A. D. Litchas

TITLE

Dist. Drilling Supervisor

DATE

5-22-70

(This space for Federal or State office use)

APPROVED

CONSENTS OF APPROVAL, IF ANY:

MAY 25 1970

R. L. BEEKMAN

ACTING DISTRICT

TITLE

RECEIVED

MAY 26 1970

*See Instructions on Reverse Side

O. C. C.
ARTESIA, OFFICE