

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TR
(Other instructi
verse side)

CATE*
on re

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SECTION, T., R., E., OR BLM. AND
SURVEY OR AREA

12. COUNTY OR PARISH 13. STATE

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) **Perforate and treat**

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Moved in workover unit, pulled rods and tubing.

2. Perforated 3-1/2" casing with one shot per interval at the following depths:
3282', 3288', 3305', 3322', 3347', 3363', 3401', 3409', 3435', 3448', 3477',
3619', 3634', 3633', 3661', 3779', 3799', 3810', 3821', a total of 19' and 19
shots.

3. Isolated and treated perforations 3799-3821' with 1,000 gallons regular 15% acid.

4. Isolated and treated perforations 3619-3661' with 1,000 gallons regular 15% acid.

5. Isolated and treated perforations 3282-3477' with 1,000 gallons regular 15% acid.

6. Treated 3-1/2" casing perforations 3282-3477' with 15,000 gallons slick water
and 15,000 20/40 sand.

7. Ran tubing and rods; pumped and tested for several days.

8. Returned well to production status April 7, 1967.

18. I hereby certify that the foregoing is true and correct

SIGNED

V. E. Fletcher

TITLE

District Superintendent

DATE

April 10, 1967

(This space for Federal or State office use)

APPROVED BY

COMMISSIONER OF APPROVAL, IF ANY:

TITLE

DATE

RECEIVED
APR 12 1967
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

APPROVED
APR 13 1967

R. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

APPROVED