SUNDRY NOTICES AND REPORTS ON WELLS. C. C.

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE.	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO PULL OR ALI'ER CASING	SUPPLEMENTARY WELL HISTORY
Perferate and Fracture I	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 13 is located 1980 ft. from $\{S\}$ line and 1980 ft. from $\{W\}$ line of sec. 14. 17-8 31-2 H.H.P.H.			Hobbs,	How Mexico	December 17	, 19. .62
	Well No. 13 is locate	d 1980 ft.	from $\{S\}$ line a	and 1980 ft. from	$ \mathbf{m} \left\{ \mathbf{W} \right\} $ line of se	c. 14
	MR/4 SM/4 See, 14	17-8	31-E	N.H.P.M.		
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)	(1/4 Sec. and Sec. No.)	(Twp.)	(Range)			
Grayburg Jackson Eddy New Maries		Ed	dy	No	w Maries	
(Field) (County or Subdivision) (State or Territory)	(Field)	(Co	ounty or Subdivision)	(State or Territory)	

The elevation of the derrick floor above sea level is ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

- 1. Hove in and rig up pulling unit.
- 2. Pull rods and tubing.
- 3. Set Baker Hetrievable Bridge Flug at approximately 3720'.
- 4. Ferferate from approximately 1504' to 3669'.
- 5. Presture with approximately 20,000 gallens sand-eil.
- 6. full retrievable bridge plug.
- 7. Return well to production.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company	Shelly Cil Company		
Address	Box 38		/ORIGINAL >
	Hobbs, New Mexico	Ву	(MISHAL) H. E. Asb
***************************************		Title	Dist. Supt.