



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLand Office Las Cruces
Lease No. 029120-19
Unit H. A. Dow "A"

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL XI	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Now "A"
Well No. 3 is located 660' ft. from N line and 1980 ft. from E line of sec. 15
SE 1/4 Sec. 15 17S 31E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Indesignated Eddy County New Mexico
(Field) (County or Subdivision) (State or Territory)
Pennsylvanian test in Grayburg-Jochum Pool
The elevation of the derrick floor above sea level is ? ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudlogging jobs, cementing points, and all other important proposed work)

To be drilled with rotary tools from surface to total depth of around 12,000' to test the Pennsylvanian formation. Casing program to be as follows:

Size hole	Size Casing	Approx. Casing Point	Sacks Cement
15"	13-3/8" OD	210'	225
12-1/4"	9-5/8" OD	3800'	2850
8-3/4"	5-1/2" OD	12000'	1200

Halliburton process will be used in cementing all casing and cement will be circulated to surface on 13-3/8" casing.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shelly Oil CompanyAddress P.O. Box 38Hobbs,New MexicoBy J. R. McGinnisTitle Dist. Superintendent