

APPROVAL
MAR 25 1963
RONNIE L. SHOOK
ACTING DISTRICT ENGINEER

(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Land Office Las Cruces
Lease No. 029420 (a)
Unit Box 36

RECEIVED
MAR 26 1963

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO ABANDON WELL	<u>Perforate & Produce</u>	<input checked="" type="checkbox"/>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hobbs, New Mexico March 22, 1963

Well No. 12 is located 1900 ft. from [N] line and 1900 ft. from [E] line of sec. 15
31/4 NE/4 Sec. 15 17-S 31-E N.M.P.M.
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)
Grayburg Jackson 3449 New Mexico
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3000 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

1. Moved in and rigged up pulling unit.
2. Set Baker Type "C" Retrievable Bridge Flag at 3196' & spotted 900 gals. Dowell 15% H E Acid.
3. Perforated 5-1/2" OD casing with 4 bullets per foot as follows: 3261-3263', 3267-3271', 3288-3292', 3297-3300', 3303-3311', 3336-3343', 3354-3358', 3403-3407', 3419-3425', 3425-3428', 3442-3446', 3464-3470' for a total of 52' and 206 holes.
4. Treated through 5-1/2" OD casing perfor. 3261-3470' (intervals) with 34,000 gallons lease oil, 20,000# 20/40 sand, 750# Adomite & 100 ball sealers by Dowell, Inc.
5. Shudd and tested well.
6. Pulled Baker Type "C" Retrievable Bridge Flag.
7. Run tubing and rods.
8. After recovering all lease oil well pumped 34 barrels of oil in 24 hours.

Date Work Performed - Feb. 16 thru 20, 1963 - Date of Potential - March 9, 1963

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Shelly Oil Company

Address Box 36

Hobbs, New Mexico

By (ORIGINAL SIGNED) H. E. Asb

Title Dist. Engt.