

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR
(Other instructions
verse side)DATE
on reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

I - Reg - 376

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FIELD OR LEASE NAME

9. WELL NO.

10. FIELD AND POOL OR WILDCAT

11. SURVEY OR AREA

12. COUNTY OR PARISH 13. STATE

1. OIL ☒ GAS ☐ OTHER ☐
WELL WELL

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☒ Perforate and treatREPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recombination Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. Moved in and rigged up workover unit, pulled rods and tubing.
2. Perforated 3-1/2" casing with one shot per interval at the following depths: 3231', 3241', 3281', 3272', 3286', 3299', 3306', 3311', 3334', 3344', 3352', 3358', 3366', 3402', 3427', 3434', 3467', 3650', 3683', 3723', 3749', 3759', 3766', 3771', and 3789', total 25' and 25 shots.
3. Isolated 3-1/2" casing perforations 3650-3789' and treated with 2,000 gallons regular 15% acid.
4. Isolated 3-1/2" casing perforations 3231-3467' and treated with 1250 gallons regular 15% acid.
5. Pulled tubing and packer and treated down 3-1/2" casing into perforations 3231-3467' with 20,000# 20/40 sand and 20,000 gallons slick water.
6. Pulled retrievable bridge plug.
7. Ran 2-3/8" tubing, rods and pump. Pumped and tested.
8. Well returned to production status April 10, 1967.

18. I hereby certify that the foregoing is true and correct

SIGNED (SIGNED) V. E. Fletcher

TITLE District Superintendent

DATE April 11, 1967.

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED
APR 14 1967
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

APPROVED

R. L. BECKMAN
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-665249

507-001

APPROVED