



Santa Fe, New Mexico

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES  
LOCATE WELL CORRECTLY

Geo. F. Getty, Inc. Carlsbad, New Mexico  
Company or Operator Address  
State "E" Well No. 1 in SW SW of Sec. 16, T. 17 S  
Lease  
R. 31 E, N. M. P. M. Grayburg-Jackson Field, Eddy County.  
Well is 990 feet south of the North line and 990 feet west of the East line of Sec. 16.  
If State land the oil and gas lease is No. B-1565 Assignment No. \_\_\_\_\_  
If patented land the owner is \_\_\_\_\_ Address \_\_\_\_\_  
If Government land the permittee is \_\_\_\_\_ Address \_\_\_\_\_  
The Lessee is Geo. F. Getty, Inc. Address Carlsbad, New Mexico  
Drilling commenced October 23, 1937 Drilling was completed Jan. 13, 1938  
Name of drilling contractor Paton Bros., Address Artesia, New Mexico  
Elevation above sea level at top of casing 3760 feet.  
The information given is to be kept confidential until 19\_\_\_\_

### OIL SANDS OR ZONES

No. 1, from 3065 to 3075 No. 4, from \_\_\_\_\_ to \_\_\_\_\_  
No. 2, from 3353 to 3362 No. 5, from \_\_\_\_\_ to \_\_\_\_\_  
No. 3, from 3495 to 3502 No. 6, from \_\_\_\_\_ to \_\_\_\_\_

### IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from 480 to 485 feet. 7 1/2 bailers per hr.  
No. 2, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_  
No. 3, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_  
No. 4, from \_\_\_\_\_ to \_\_\_\_\_ feet. \_\_\_\_\_

### CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
10"	38#	8	Youngtn.	576	Tex. Pat.				Water shut off Oil Stream.
7"	24#	8	Youngtn.	3046	Float				

### MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12"	10"	576	50	Halliburton	none	none
10"	7"	3046	100	Halliburton		2 tons

### PLUGS AND ADAPTERS

Heaving plug—Material \_\_\_\_\_ Length \_\_\_\_\_ Depth Set \_\_\_\_\_  
Adapters—Material \_\_\_\_\_ Size \_\_\_\_\_

### RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		25% Acid	1000	1-15-38	T.D.	T.D.
		25% Acid	3000	1-25-38	T.D.	T.D.

Results of shooting or chemical treatment First Treatment, - no result.  
Second Treatment, - increased flow 100 bbls. Oil, 45000 cu.ft. Gas.

### RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

### TOOLS USED

Rotary tools were used from \_\_\_\_\_ feet to \_\_\_\_\_ feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet  
Cable tools were used from 0 feet to 3567 feet, and from \_\_\_\_\_ feet to \_\_\_\_\_ feet

### PRODUCTION

Put to producing January 26, 1938  
The production of the first 24 hours was 100 (20 hrs) barrels of fluid of which 100% was oil; \_\_\_\_\_% emulsion; no. \_\_\_\_\_% water; and no. \_\_\_\_\_% sediment. Gravity, Ba 37.8  
If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft. of gas \_\_\_\_\_  
Rock pressure, lbs. per sq. in. \_\_\_\_\_

### EMPLOYEES

F. A. Burks Driller Jim Hammond Driller  
O. H. Stewart Driller \_\_\_\_\_ Driller

### FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 1 st  
day of February, 1938  
SEAL  
W. O. Montgomery  
Notary Public  
My Commission expires 2-22-41

Place \_\_\_\_\_ Date \_\_\_\_\_  
Name Leo R. Manning  
Position Supv Agent  
Representing Geo. F. Getty, Inc.,  
Company or Operator  
Address Carlsbad, New Mexico

FROM	TO	THICKNESS IN FEET	FORMATION
0	60		Sand
60	240		Red beds
240	260		Red sand
260	305		Red beds
305	335		Anhy
335	340		Red beds
340	355		Red sand
355	395		Lime & Anhy
395	480		Red bed
480	485		Lime
485	525		Red beds
525	545		Anhy
545	1425		Salt
1425	1437		Anhy and Red Rock
1437	1450		Salt
1450	2500		Anhy with traces of lime
2500	2537		Red beds
2537	2705		Lime
2705	2791		Anhy with traces of lime
2791	2962		Lime
2962	2972		Sand
2972	3353		Lime
3353	3362		Sand
3362	3567		Lime
3567			Total depth