


FORMATION RECORD
NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico



WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Marchison & Clewitt, Inc. Artesia, N. M. Box 555
Company or Operator Address
State Well No. 2-8 in NW SW SE of Sec. 16 T. 17S
Lease
R. 31E N. M. P. M. Grayburg-Washburn Field, Lady County.
Well is 4290 feet south of the North line and 2310 feet west of the East line of Sec. 16
If State land the oil and gas lease is No. Assignment No.
If patented land the owner is Address
If Government land the permittee is Address
The Lessee is Address
Drilling commenced Nov. 5 1940 Drilling was completed Jan. 11 1941
Name of drilling contractor Welch Drilling Co. Address Artesia, N. M.
Elevation above sea level at top of casing 3590 feet.
The information given is to be kept confidential until 19

OIL SANDS OR ZONES

No. 1, from 2840 to 2845 No. 4, from to
No. 2, from 3112 to 3115 No. 5, from to
No. 3, from 3590 to 3600 No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.
No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM TO	PURPOSE
8 5/8	24#			587	H			Surface
7"OD	20#			2983	H			Oil

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
10"	8"	587	50	Hallibarton		
8"	7"	2983'	100	"	heavy	40 sax.

PLUGS AND ADAPTERS

Heaving plug—Material Length Depth Set
Adapters—Material Size

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Acid	500	1/4	3645	same
		"	1000	1/5	3645	"
		"	2000	1/7	3645	"

Results of shooting or chemical treatment Very little increase

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet
Cable tools were used from 0 feet to 3645 feet, and from feet to feet

PRODUCTION

Put to producing Jan. 13 1941
The production of the first 24 hours was 65 barrels of fluid of which % was oil; % emulsion; % water; and % sediment. Gravity, Be.
If gas well, cu. ft. per 24 hours Gallons gasoline per 1,000 cu. ft. of gas
Rock pressure, lbs. per sq. in.

EMPLOYEES

F. H. Grant Driller Mount Driller
C. M. Oliver Driller Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 13 Artesia, N. M. Jan. 13, 1941
day of January 1941 Place Date
Name Marvin H. Sanders

FORMATION RECORD

FORM 1-102

FROM	TO	THICKNESS IN FEET	FORMATION
0	20		Blow Sand
20	335		Red Bed
335	410		Gyp
410	450		Anhydrite
450	520		Gyp
520	545		Red Bed
545	1483		Salt
1483	1700		Anhydrite
1700	1740		Broken Anhydrite
1740	2210		Anhydrite (show oil 2160-2185 & oil show.)
2210	2220		Broken line
2220	2265		Anhydrite
2265	2275		Brown line
2275	2358		Anhydrite
2358	2370		Anhydrite & red sand
2370	2385		Anhydrite
2385	2405		Anhydrite & red sand
2405	2445		Anhydrite
2445	2475		Anhydrite & red breaks
2475	2593		Anhydrite
2593	2627		red sand
2627	2685		Anhydrite
2685	2690		red sand
2690	2750		Anhydrite
2750	2760		gray line
2760	2830		Anhydrite
2830	2840		line
2840	2850		Oil sand & anhydrite (show oil 2840-5)
2850	2875		Anhydrite
2875	2900		Anhydrite & red breaks
2900	2945		Anhydrite
2945	2960		gray line
2960	2965		gray sand
2965	2982		Anhydrite
2982	3001		line
3001	3021		gray line
3021	3042		line
3042	3346		line (show oil 3112-15)
3346	3355		Anhydrite
3355	3645		line (T.D.) (oil & gas 3590-3600)
CASING RECORD			
MUDGING AND CEMENTING RECORD			
PLUGS AND ADAPTERS			
RECORD OF SHOOTING OR CHEMICAL TREATMENT			
RECORD OF DRILL STEM AND SPECIAL TESTS			
TOOLS USED			
EMPLOYEES			