

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE
(Other instructions
reverse side)ICATE
on re-Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

LC 029395 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Turner "B"

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 17, T17S, R31E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Atlantic Richfield Company

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL, 660' FWL (Unit Letter L)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3696' Grd.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Convert to Water Inj.

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*In accordance w/NMOCC Order No. R-3185 dated 2/1/67, we propose to con-
vert this well to water injection as follows:

1. Clean out to original T.D. of 3461'.
2. Run 4½" OD 8R 9.5# ST&C new casing to T.D. and cement w/200 sx of Class "C" cement. WOC 18 to 24 hrs. Test casing to 1500#.
3. Run GR-Correlation log and perforate Jackson zone w/one 0.42" jet @ 3346, 3350, 3357, 3373, 3374, 3379, 3381, 3390, 3392, 3394, 3396, 3398, 3400, 3402, 3416, 3421, 3426, 3428, 3430, 3432, 3433, 3434, 3440, 3442, 3444, 3446, 3448 and 3450' (28 holes, GR-N log).
4. Treat w/3500 gallons 15% HCl acid and ball sealers.
5. Run tension packer on 2-3/8" tubing and set at 3300'. Load annulus w/treated fresh water.
6. Start water injection.

Work to start about 1/15 DEC.

RECEIVED

DEC 15 1969

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

A. D. Breche

TITLE

Dist. Drlg. Supervisor

DATE

12-12-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
DEC 15 1969
R. L. BECKMA

*See Instructions on Reverse Side