

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYDRAFT
SUBMIT TO TR
AROBG instruct.
verse 486 NM
DATE
on re
88210Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 049988-A

6. IF INDIAN, NAME OF INDIAN PRIZE NAME

APR 29 1983

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

ARTESIA OFFICE
Foster Eddy

9. WELL NO.

4

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson (Q.G.S.A.)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 17 T-17-S, R-31-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Sun Exploration & Production Co. ✓

3. ADDRESS OF OPERATOR

P.O. Box 1861, Midland, TX 79702

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

660' FNL & 1980' FWL

OCT 1 1982
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3710 DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 9-8 MIRU. Unable to rlse Baker AD-1 tension pkr, push pkr down hole to 2869, unable to free pkr. Broke safety jt, POH, lay down 91 jts 2 3/8 tbg, & safety jt. RIH w/7" gage ring (on wire line) to 2850', ran & set 7" go w/ CIBP 2850, shut off wtr flow immediately dump 7 sx cmt top CIBP back to 2815'.
- 9-9 RIH w/7" FB pkr, 2 3/8 tbg, set pkr 2801, test CIBP 1000# ok, set pkr at various depths isolate csg. lk 1087. Rlse pkr, POH w/pkr & 2 3/8 tbg. Perf 4 sqz. holes 1350-1351, RIH 7" Howco EZY-Drill cem., Ret, 2 3/8 tbg, set cmt ret 1018', test tbg 3000# ok, mix & pump 100 sx class "C" cmt over disp'l cem. ret 1/2 bbl. Snap out cem ret. PU 960'.
- 9-10 Lower stinger sub. sting into cem. ret 1018. Attempt pressure sqz. circ out 7" csg., attempt to pressure csg, circ out tbg. PU to 987, spot 10 sx cmt. Plug on cem. ret. back to 965'. POH w/stinger sub, 2 3/8 tbg., perf. 4 sqz. holes 550-551, RIH w/7" tension pkr, 2 3/8 tbg, set pkr 310', EIR thru perfs. Circ out braden head cmt w/100 sx class "C" cmt, disp'l to 448'.
- 9-11 Unable to unset pkr. Pressup on tbg to 1000#, tested backside to 1000#, both tested OK. Unscrewed safety jt off pkr. POH w/2 3/8 tbg. Cut W.H. off. Spotted 15 sx surface plug. Installed dryhole marker.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Accounting Asst. II

DATE 9-28-82

(This space for Federal or State Office Use)

APPROVED BY W. CHESTER
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APR 27 1983

*See Instructions on Reverse Side