Form 3160-5 (June 1990)

UNITED STATES DEPARTN IT OF THE INTERIOR N.M. Oil As. Division BUREAU OF LAND MANAGEMENT 811 S. 1st Street FORM APPROVED Budget Bureau No. 1004-01 Expires March 31, 1993

FORM	APPROVE	ED O
Jdget Bur	eau No. 1004-	0135

2. Name of Corporate / DEVON ENERGY CORPORATION (NEVADA) RECEIVED Hudson Federal #2	SUNDRY NOTICES	5. Lease Designation and Serial No.			
SUBMIT IN TRIPLICATE Type of Well					
Type of Well	Use "APPLICATION FO	6. If Indian, Allottee or Tribe Name			
Type of Well	SUBMIT IN TRIPLICATE				
Same of Operator DEVOR ENERGY CORPORATION (NEVADA) SECTIVE Section 18.2			7. If Unit or CA, Agreement Designation		
DEVOK ENERGY CORPORATION (NEVADA) DECCIVED Hudson Federal #2 9. AFF Will No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 255-3611 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 10. Field and Fool, or Exploratory Area Grayburg-Jackson Field 11. County or Parish, Saite Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION Abandonment Subsequent Report Plugging Back Cassing Repair Altering Casing Conversion to lipiction Other Office Report reside of majoric conversion to lipiction Discontine Proposed or Completed Operations (Cherry state all pertinent details, and give and	Well Well Cother	<u> </u>	9 Well Name and No.		
3. Address and Telephone No. 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-2611 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) 5. Location of Well (Footage. Sec., T., R., M., or Survey Description) 6. Location of Well (Footage. Sec., T., R., M., or Survey Description) 7. Location of Well (Footage. Sec., T., R., M., or Survey Description) 7. Location of Well (Footage. Sec., T., R., M., or Survey Description) 8. Location of Well (Footage. Sec., T., R., M., or Survey Description) 8. Location of Well (Footage. Sec., T., R., M., or Survey Description) 9. Left and Total Country (Inc. M.) 10. Location of Well (Footage. Sec., T., R., M., or Survey Description) 11. Location of Well (Footage. Sec., T., R., M., or Survey) 12. Location of Well (Footage. Sec., T., R., M., or Survey) 13. Location of Well (R., Survey) 13. Describe Proposed or Completed Operation (Clearly state all pertinent details, and give pertinent dates. including estimated date of stating any proposed work. If well is directionally defiled, a showledge of the survey proposed work. If well is directionally defiled, a showledge of the survey proposed work. If well is directionally defiled, a showledge of the survey proposed work. If well is directionally defiled, a showledge of the survey proposed work. If well is directionally defiled, a showledge of the survey proposed work. If well is directionally defiled, a showledge of the survey proposed work. If well is directionally defiled, a showledge of the survey proposed work. If well is directionally defiled, a showledge of the survey proposed work. If well is directionally defiled, a showledge		.:			
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 10. Field and Pool. or Exploratory Area 10. Field and Pool. or Exploratory Area 11. Country or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION TYPE OF ACTION Notice of Inent Abandonment Recompletion Recompletion Report Plugging Back Casing Repair Casing Repair Casing Repair Altering Casing Conversion to Injection Other Discrete Proposed or Completed Operations (Clearly state all pertitient details, and give pertitient date, including estimated date of starting any proposed work. If well is directionally drilled, a substraftic locations and measured and true vertical depths for all markers and zones profitient to this work.)* Well was permanently plugged and abandoned as follows: 05/07/99 - Set cernent retainer @ 2400'. 06/24/99 - Pump 250 sxs cernent below retainer. 06/25/99 - Perforate 7" casing @ 1350'(50' below base of salt). Discovered casing leaks in 7" casing @ 378' and 409'. 06/29/99 - Set cernent retainer @ 1260', pump 75 sxs class "C" cernent below retainer. Pump 100 sxs class "C" cernent and displace to 275'(tagged) inside of 7" casing. Spot cernent plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. Abortived as to programs of the well bord. Substrate restoration is completed. Abortived as to program of the well bord. Abort	3. Address and Telephone No.				
Grayburg-Jackson Field 11. County or Parish, State Eddy County, NM	20 NORTH BROADWAY, SUITE 1500, O	30-015-05209			
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION Abandonment Recompletion New Construction	4. Location of Well (Footage. Sec., T., R., M., or Survey	10. Field and Pool, or Exploratory Area			
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION Abandonment Change of Plans	1650'FNL & 990'FEL of Section 18-T17S-F	Grayburg-Jackson Field			
CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent			11. County or Parish, State		
TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent			Eddy County, NM		
TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Recompletion Reco	CHECK APPROPRIATE BOX(s	s) TO INDICATE NATURE OF NOTICE, REP	PORT OR OTHER DATA		
Notice of Intent					
Recompletion New Construction New Construction New Construction Plugging Back Non-Routine Fracturing Water Shut-Off Casing Repair Water Shut-Off Water Shut-	Notice of Intent				
Casing Repair Water Shut-Off Conversion to Injection Dispose Water Chore Report result of multiple completion on Wall Completion of Recompletion of Recompletion on Placement In Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, g subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) Well was permanently plugged and abandoned as follows: 05/07/99 - Set cerment retainer @ 2400'. 06/24/99 - Pump 250 sxs cerment below retainer. 06/25/99 - Perforate 7" casing @ 1350'(50' below base of salt). Discovered casing leaks in 7" casing @ 378' and 409'. 06/29/99 - Set cerment retainer @ 1260', pump 75 sxs class "C" cerment below retainer. Pump 100 sxs class "C" cerment and displace to 275'(tagged) inside of 7" casing. Spot cerment plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. Positive of as to plugging of the wall back. Liabity under bond is retained until back. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. I hereby certify that the foregoing is true and correct Charles H. Carleton Title Sr. Engineering Tech. Date June 30, 1999 Title Part Note of the Carls of the subsequent procedure was positive and correct of the carls of the subsequent procedure was positive positive specified use) (ORIG. SGD.) DAVID R. GLASS Title Part Note of the Carls of the subsequent positive specified use) (ORIG. SGD.) DAVID R. GLASS	Trouble of Intell				
Final Abandonment Notice	Subsequent Report	1	=		
Other Dispose Water Note: Report results of multiple completion or well completion or Substantial Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, g substantial date of starting any proposed work. If well is directionally drilled, g well was permanently plugged and abandoned as follows: 05/07/99 - Set cement retainer @ 2400'. 06/24/99 - Pump 250 sxs cement below retainer. 06/25/99 - Perforate 7" casing @ 1350'(50' below base of salt). Discovered casing leaks in 7" casing @ 378' and 409'. 06/29/99 - Set cement retainer @ 1260', pump 75 sxs class "C" cement below retainer. Pump 100 sxs class "C" cement and displace to 275'(tagged) inside of 7" casing. Spot cement plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. Install dry hole marker and prepare to restore location. NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. Thereby certify that the foregoing is true and correct Charles H. Carleton Title Sr. Engincering Tech. Date June 30, 1999 Title Sr. Engincering Tech. Date June 30, 1999 Title Sr. Engincering Tech. Date June 30, 1999		Casing Repair	Water Shut-Off		
Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, g subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Well was permanently plugged and abandoned as follows: 05/07/99 - Set cement retainer @ 2400'. 06/24/99 - Pump 250 sxs cement below retainer. 06/25/99 - Perforate 7" casing @ 1350'(50' below base of sait). Discovered casing leaks in 7" casing @ 378' and 409'. 06/29/99 - Set cement retainer @ 1260', pump 75 sxs class "C" cement below retainer. Pump 100 sxs class "C" cement and displace to 275'(tagged) inside of 7" casing. Spot cement plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. Approved as to plugging of the wall back. Labelly under bond is retained unall surface restoration is completed. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. Thereby certify that the foregoing is true and correct	Final Abandonment Notice	1 = -	Conversion to Injection		
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, g subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Well was permanently plugged and abandoned as follows: 05/07/99 - Set cernent retainer @ 2400'. 06/24/99 - Pump 250 sxs cernent below retainer. 06/25/99 - Perforate 7" casing @ 1350'(50' below base of salt). Discovered casing leaks in 7" casing @ 378' and 409'. 06/29/99 - Set cernent retainer @ 1260', pump 75 sxs class "C" cernent below retainer. Pump 100 sxs class "C" cernent and displace to 275'(tagged) inside of 7" casing. Spot cernent plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. NOTE: 1. 9.5ppg mud spotted between cernent plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. Thereby certify that the foregoing is true and correct Charles H. Carleton Signed Approved by (ORIG, SGD.) DAVID R. GLASS Title FETROLEUM ENGINEER Date June 30, 1999 Title Part Cleum Engineering Tech. Date June 30, 1999 Title Part Cleum Engineering Tech. Date June 30, 1999		Other	—— ·		
Well was permanently plugged and abandoned as follows: 05/07/99 - Set cement retainer @ 2400'. 06/24/99 - Pump 250 sxs cement below retainer. 06/25/99 - Perforate 7" casing @ 1350'(50' below base of salt). Discovered casing leaks in 7" casing @ 378' and 409'. 06/29/99 - Set cement retainer @ 1260', pump 75 sxs class "C" cement below retainer. Pump 100 sxs class "C" cement and displace to 275'(tagged) inside of 7" casing. Spot cement plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. Thereby certify that the foregoing is true and correct Charles H. Carleton Signed Abult Hollow (ORIG. SGD.) DAVID R. GLASS Title Sr. Engineering Tech. Date June 30, 1999 Title Sr. Engineering Tech. Date June 30, 1999 Title Correction is Completed. Title Sr. Engineering Tech. Date June 30, 1999 Title Sr. Engineering Tech. Date June 30, 1999	12. Describe Proceed or Completed Occuptions (Clearly state all		Completion or Recompletion Report and Log form.)		
05/07/99 - Set cement retainer @ 2400'. 06/24/99 - Pump 250 sxs cement below retainer. 06/25/99 - Perforate 7" casing @ 1350'(50' below base of salt). Discovered casing leaks in 7" casing @ 378' and 409'. 06/29/99 - Set cement retainer @ 1260', pump 75 sxs class "C" cement below retainer. Pump 100 sxs class "C" cement and displace to 275'(tagged) inside of 7" casing. Spot cement plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. I hereby certify that the foregoing is true and correct Charles H. Carleton Signed Charles H. Carleton Title Sr. Engineering Tech. Date June 30, 1999 (ORIG. SGD.) DAVID R. GLASS Title Ti			any proposed work. If well is directionally drilled, give		
06/24/99 - Pump 250 sxs cement below retainer. 06/25/99 - Perforate 7" casing @ 1350'(50' below base of salt). Discovered casing leaks in 7" casing @ 378' and 409'. 06/29/99 - Set cement retainer @ 1260', pump 75 sxs class "C" cement below retainer. Pump 100 sxs class "C" cement and displace to 275'(tagged) inside of 7" casing. Spot cement plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. I hereby certify that the foregoing is true and correct Charles H. Carleton Signed — White Halliam — Title Sr. Engineering Tech. — Date June 30, 1999 (ORIG. SGD.) DAVID R. GLASS Title — TROLEUM ENGINEER Date Jule 1 3 1999	Well was permanently plugged and abando	oned as follows:			
O6/25/99 - Perforate 7" casing @ 1350'(50' below base of salt). Discovered casing leaks in 7" casing @ 378' and 409'. O6/29/99 - Set cement retainer @ 1260', pump 75 sxs class "C" cement below retainer. Pump 100 sxs class "C" cement and displace to 275'(tagged) inside of 7" casing. Spot cement plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. Thereby certify that the foregoing is true and correct Charles H. Carleton Signed Abdubblication Title Sr. Engineering Tech. Date June 30, 1999	05/07/99 - Set cement retainer @ 2400'.				
O6/29/99 - Set cement retainer @ 1260', pump 75 sxs class "C" cement below retainer. Pump 100 sxs class "C" cement and displace to 275'(tagged) inside of 7" casing. Spot cement plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. Thereby certify that the foregoing is true and correct Charles H. Carleton Title Sr. Engineering Tech. ORIG. SGD.) DAVID R. GLASS Title PETROLEUM ENGINEER Date June 30, 1999 Title PETROLEUM ENGINEER	06/24/99 - Pump 250 sxs cement below re	tainer.			
Pump 100 sxs class "C" cement and displace to 275'(tagged) inside of 7" casing. Spot cement plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. Thereby certify that the foregoing is true and correct Charles H. Carleton Title Sr. Engineering Tech. ORIG. SGD.) DAVID R. GLASS Title PETROLEUM ENGINEER Date June 30, 1999 Title June 30, 1999	06/25/99 - Perforate 7" casing @ 1350'(50'	below base of salt). Discovered casing leaks in 7	" casing @ 378' and 409'.		
Pump 100 sxs class "C" cement and displace to 275'(tagged) inside of 7" casing. Spot cement plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. Thereby certify that the foregoing is true and correct Charles H. Carleton Title Sr. Engineering Tech. ORIG. SGD.) DAVID R. GLASS Title PETROLEUM ENGINEER Date June 30, 1999 Title PETROLEUM ENGINEER Date June 30, 1999	06/29/99 - Set cement retainer @ 1260', pu	ump 75 sxs class "C" cement below retainer.	Pact ID-2		
Spot cement plug 0'- 50' in 7" casing. Install dry hole marker and prepare to restore location. NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. Thereby certify that the foregoing is true and correct Charles H. Carleton Title Sr. Engineering Tech. Date June 30, 1999 (ORIG. SGD.) DAVID R. GLASS Title PETROLEUM ENGINEER Date JUL 13 1999	Pump 100 sxs class "C" cement	and displace to 275'(tagged) inside of 7" casing.	7-31-99		
NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. I hereby certify that the foregoing is true and correct Charles H. Carleton Signed Audit Multipul Title Sr. Engineering Tech. ORIG. SGD.) DAVID R. GLASS Approved by ORIG. SGD.) DAVID R. GLASS Title TROLEUM ENGINEER Date June 30, 1999	Spot cement plug 0'- 50' in 7" casing. $\mathcal{L}_{\mathcal{F}}$				
NOTE: 1. 9.5ppg mud spotted between cement plugs. 2. Due to casing leaks, in 7" casing, P&A procedure was modified from the original intent. Subsequent procedure was verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. Thereby certify that the foregoing is true and correct Charles H. Carleton Signed Ault Holder Title Sr. Engineering Tech. ORIG. SGD.) DAVID R. GLASS Approved by Title TROLEUM ENGINEER Date Jule 13 1999	install dry hole marker and prepare	ting of this well born.			
verbally approved by Joe Lara (BLM-Carlsbad, NM office). 14. I hereby certify that the foregoing is true and correct Charles H. Carleton Signed Audio Holder Use (Charles of Federal or State Office use) Approved by (ORIG. SGD.) DAVID R. GLASS Title FETROLEUM ENGINEER Date Date Date Date Date Date Date Date					
Charles H. Carleton Signed Aults Halton Title Sr. Engineering Tech. ORIG. SGD.) DAVID R. GLASS Title TROLEUM ENGINEER Date June 30, 1999 Title Date June 30, 1999	2. Due to casing leaks, in 7" casing	, P&A procedure was modified from the original in	tent. Subsequent procedure was		
Charles H. Carleton Signed Author State Office use) Approved by ORIG. SGD.) DAVID R. GLASS Title Sr. Engineering Tech. Date June 30, 1999 Title FETROLEUM ENGINEER Date JUL 1 3 1999	verbally approved by Joe Lara (E	BLM-Carlsbad, NM office).			
Title Sr. Engineering Tech. ORIG. SGD.) DAVID R. GLASS Title Sr. Engineering Tech. Date June 30, 1999	14. I hereby certify that the foregoing is true and correct				
(This space for Federal or State of fice use) Approved by (ORIG. SGD.) DAVID R. GLASS Title FETROLEUM ENGINEER Date JUL 13 1999		Charles H. Carleton			
Approved by (ORIG. SGD.) DAVID R. GLASS Title FETROLEUM ENGINEER Date JUL 13 1999		Title Sr. Engineering Tech.	Date June 30, 1999		
Approved by Date	, ,	ACC	PRO FIG. SEC.		
······································	ORIG. SGD.) DAVID H. GL	ASS PETROLEUM ENGIN	EEF Date JUL 13 1999		
	• • • • • • • • • • • • • • • • • • • •				