

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instructions on reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029395-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Turner A

9. WELL NO.

8

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

18-T17S-R31E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Sinclair Oil &amp; Gas Company

3. ADDRESS OF OPERATOR

P. O. Box 1920, Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface

1980' fr the East line and 660' fr the South line

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3691' GR

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON\* ☐CHANGE PLANS ☐

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☒(Other) ☐

Deepening

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT\* ☐☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-10-66 Rigged up unit and drilled Gray Lime from 3448' to 3598' Total Depth.  
to Swabbed and tested.

11-14-66

11-15-66 Swabbing and testing.

to

12-12-66

12-13-66 Acidized Grayburg open hole 3425-3470' w/500 gals. regular 15% acid Max.

to

12-15-66 Pressure 3200#, Min. 3100# @ 1 BPM. ISIP 2500#, 5 mins. SIP Vacuum. Swabbed  
12 BAW plus 19 BLW in 4-1/2 hrs., swabbed 1 BFW in 1/2 hr. and swabbed down,  
fillup to 400' from bottom in 1 hr.12-16-66 Spot 20 sacks Incor Neat Cement 3598-3522', WOC 24 hrs. Swabbed Grayburg  
open hole 2918-3522' 134 BFW in 10 hrs. Fluid level 1800' from surface.

12-18-66 Spot 15 sacks cement 3522-3440', WOC 24 hrs. and drilled cement to PBTD 3462'.

12-21-66 Sand Water Frac Grayburg Open-Hole 3314-3462' w/5000 gals. celled water and  
5000# sand w/Max. Press. 3800# @ 20 BPM. Swabbed & tested.1-11-67 On potential test pumped Grayburg Open-Hole 2918-3462' 3 BNO plus 27 BFW  
in 24 hrs. GOR 330:1. Recompleted in Grayburg Open-Hole 2918-3462' after  
deepening 150' to 3598' and plugging back to 3462'.

RECEIVED

JAN 17 1967

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Superintendent

DATE

1-12-67

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JAN 16

R. L. DECKMAN

ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side

Orig &amp; 2cc: USGS Artesia

cc: Regional Office

cc: file