

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved. C. H. F. S. F.
Budget Bureau No. 42-R1424.5. LEASE DESIGNATION AND SERIAL NO.
LC 029548 (A)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		3. IF INDIAN, ALLOTTEE OR TRIBE NAME	
2. NAME OF OPERATOR ATLANTIC RICHFIELD COMPANY		7. UNIT AGREEMENT NAME	
3. ADDRESS OF OPERATOR P. O. Box 1920, Hobbs, New Mexico 88240		8. FARM OR LEASE NAME C. A. Russell	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' fr North line and 1980' fr East line of Sec. 18-T17S-R31E		9. WELL NO. 9	
14. PERMIT NO.		10. FIELD AND POOL, OR WILDCAT Grayburg Jackson	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3705' GR		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 18-T17S-R31E	
		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other) Run 4-1/2"OD Csg. cement &

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

x Perf. Acidize

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3495'. PBSD 3486'. Well presently completed in Grayburg San Andres ~~perforated~~ Open Hole 2850'-3486'. Producing 35 BOPD and 97 BOPD.
8-5/8"OD 32# Csg. set @ 605' w/50 sacks cement.
7"OD 24# csg. set @ 2850' w/100 sacks cement.
7"OD casing found to be collapsed.

PROPOSE TO: Run 4-1/2"OD 9.5# J-55 casing set @ approx. 3486' and cement w/160 sacks Incor Cl. C cement plus 4% gel plus 1/4#/sk. Flo-Seal, followed by 50 sacks Incor Cl. C neat. Circulate to surface. Drill cement to 3475', run depth control log and perforate the following intervals approx. 3410-3435' & 3456-3465' Grayburg San Andres. Acidize San Andres perfs. w/approx. 2,000 gallons 15% NE acid and swab back acid and load, return to production.

MAR 26 1969

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Superintendent

DATE 3-21-69

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

Orig&4cc: USGS, Artesia
cc: Southern Region (West Set Instructions on Reverse Side)
cc: file