

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE
(Other Instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 029395 (a)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Water Injection Well

2. NAME OF OPERATOR

Atlantic Richfield Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

2200' FSL, 440' FWL (Unit Letter L)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3761' Grd.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Turner "A"

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 18, T17S, R31E

12. COUNTY OR PARISH
Eddy13. STATE
N.M.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Run 4½" Inner String

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Tracer surveys show that injected water is not going into the desired zones. We propose to run 4½" OD 8R 9.5# J-55 ST&C casing to T.D. and cement w/150 sx salt saturated Class "C" cement. Calculated top of cement to be 2500'. Perforate w/one 0.42" jet shot @ 3373, 3378, 3389, 3392, 3394, 3398, 3402, 3410, 3412, 3414, 3416, 3418, 3425, 3432, 3441, 3442, 3448, 3458, 3464, 3471, 3474, 3483, 3485, 3490 and 3498. Treat these perforations w/3500 gallons 15% HCl acid and ball sealers. Run 2-3/8" tubing and tension packer. Load annulus w/treated fresh water and set packer at approximately 3300'. Resume water injection. Work will start when approval is obtained.

RECEIVED
NOV 24 1969U. S. GEOLOGICAL SURVEY
ARTESIAN OFFICERECEIVED
NOV 25 1969
U. S. GEOLOGICAL SURVEY
ARTESIAN OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Dist. Drlg. Supervisor

DATE

11-21-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side