

N

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

30-015-05234

## WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPPLICATE. FORM C-110 WILL NOT BE APPROVED UNTIL FORM C-105 IS PROPERLY FILLED OUT.

AREA 640 ACRES  
LOCATE WELL CORRECTLYSouthern Production Company, Inc.  
(Danciger Oil & Refining Company)

Fort Worth, Texas

Address

Turner

Well No.

A-5

in NW NW

of Sec.

19

T. 17-S

Lease

R. 31-E, N. M. P. M., Grayburg-Jackson Field, Eddy County.

Well is 330 feet south of the North line and 660 feet west of the East line of NW NW Sec. 19

If State land the oil and gas lease is No. Assignment No.

If patented land the owner is. Address.

If Government land the permittee is. Mancil E. Turner, Address. Artesia, N. M.

The Lessee is Southern Production Company, Inc., Address. Fort Worth, Texas

Drilling commenced. July 20, 1939. Drilling was completed. September 28, 1939

Name of drilling contractor. Kersey, Address. Artesia, N.M.

Elevation above sea level at top of casing. 3733 feet.

The information given is to be kept confidential until 19.

## OIL SANDS OR ZONES

No. 1, from 1845 to 1850 No. 4, from 2834 to 2838

No. 2, from 1928 to 1936 No. 5, from 3136 to 3146

No. 3, from 2585 to 2595 No. 6, from 3409 to 3415

## IMPORTANT WATER SANDS

3440 3445  
3480 3495

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet.

No. 2, from to feet.

No. 3, from to feet.

No. 4, from to feet.

## CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED		PURPOSE
							FROM	TO	
8-5/8"	32#	8	Bethlehem	550'					
7" O.D.	24#	10	Youngstown	3014'					
			Seamless						

## MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHODS USED	MUD GRAVITY	AMOUNT OF MUD USED
	8-5/8"	550'	50	Halliburton		No Mud
	7" O.D.	3014'	100	Halliburton	9-1/2#, 30 Viscosity	5 Tons

## PLUGS AND ADAPTERS

Heaving plug—Material. Length. Depth Set.

Adapters—Material. Size.

## RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT

Results of shooting or chemical treatment.

## RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

## TOOLS USED

Rotary tools were used from feet to feet, and from feet to feet

Cable tools were used from 0 feet to 3518 feet, and from feet to feet

## PRODUCTION

Put to producing. September 28, 1939

The production of the first 24 hours was 257 barrels of fluid of which 100% was oil; 0% emulsion; 0% water; and 0% sediment. Gravity, Be.

If gas well, cu. ft. per 24 hours. Gallons gasoline per 1,000 cu. ft. of gas.

Rock pressure, lbs. per sq. in.

## EMPLOYEES

Contracted to: Driller

Kersey, Driller

## FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Subscribed and sworn to before me this 13th

day of November, 1939

MAXINE FOWLER, NOTARY PUBLIC IN AND FOR TARRANT COUNTY, TEXAS  
My Commission expires JUN 1953

Fort Worth, Texas November 13, 1939

Name. Agent

Position. Southern Production Company, Inc.

Representing. (Danciger Oil &amp; Refining Company)

Address. P. O. Box 670, Fort Worth, Texas

## FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION
0	175	175	Sandy Soil
175	245	70	Gyp & Red Shale
245	260	15	Red Shale
260	380	120	Anhydrite
380	420	40	Gyp
420	450	30	Anhydrite
450	510	60	Red Bed
510	518	8	Gyp
518	1190	672	Salt
1190	1240	50	Salt & Shells
1240	1250	10	Salt
1250	1425	175	Anhydrite
1425	1465	40	Anhydrite & Red Bed
1465	1545	80	Red Bed
1545	2135	590	Anhydrite (Oil Show 1845-1850) (Oil & Gas Show 1928-1936)
2135	2160	25	Anhydrite & Red Bed
2160	2340	180	Anhydrite
2340	2370	30	Sand
2370	2450	80	Anhydrite
2450	2465	15	Lime
2465	2730	265	Anhydrite (Oil Show 2585-2595) (Show of Oil & Increase in Gas 2834-2838)
2730	2961	231	Sandy Lime
2961	3505	544	Lime (Oil Shows: 3136-3146; 3409-3415; 3440-3445; 3480-3495)
3505	3508	3	Soft Lime
3508	3512	4	Very Soft Lime
3512	3518	6	Soft Lime
			Total Depth