

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 1
(Other Instru s on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.5. LEASE DESIGNATION AND SERIAL NO.
LC 029395 (a)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Turner "A"9. WELL NO.
5

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 19, T17S, R31E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER Water Injection Well

2. NAME OF OPERATOR

Atlantic Richfield Company

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

330' FNL, 660' FWL (Unit Letter D)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3733' Grd.

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Run 4½" Inner String

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

Tracer surveys show that injected water is not going into the desired zones. We propose to run 4½" OD 8R 9.5# J-55 ST&C casing to original T.D. of 3520' and cement w/150 sx of salt saturated cement. Perforate w/one 0.42" jet shot @ 3364, 3365, 3373, 3384, 3389, 3393, 3402, 3404, 3407, 3412, 3413, 3427, 3433, 3434, 3440, 3444, 3452, 3453, 3459, 3462, 3466, 3467, 3468, 3478, 3480, 3484, 3486 and 3489'. (28 holes - GR-N log.) Treat w/3500 gallons 15% HCl acid & ball sealers. Run 2-3/8" tubing and tension packer. Load annulus w/treated fresh water, set packer at approximately 3300' and resume water injection. Work to start about 12/1/69

RECEIVED

NOV 24 1969

U. S. GEOLOGICAL
SURVEY

RECEIVED

NOV 25 1969

C. C.
OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

L. D. Kitcher

TITLE Dist. Drlg. Supervisor

DATE 11-21-69

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side