Form 3160-5 (June 1990)

any matter within its jurisdiction.

UNITED STATES DEPARTME... OF THE INTERIOR BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division FORM APPROVED
811 S. 1st Street
Budget Bureau No. 1004-0135

4/5F

Expires March 31, 1993 SUNDRY NOTICES AND REPORTS ON WELLS Artesia, NM 8821 (1-2834se Designation and Serial No. Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. LC-029395A 6. If Indian, Allottee or Tribe Name Use "APPLICATION FOR PERMIT—" for such proposals SUBMIT IN TRIPLICATE 7. If Unit or CA, Agreement Designation 1. Type of Well ☐ Gas Other WIW Oil 8. Well Name and No. OPERATOR OPERATOR (NO. 1911) Turner "A" #15 9. API Well No. 3. Address and Telephone No 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611 30-015-05240 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage. Sec., T., R., M., or Survey Description) Grayburg-Jackson Field 1650' FNL & 1980' FWL of Section 19-T17S-R31E 11. County or Parish, State Eddy County, NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION TYPE OF SUBMISSION Notice of Intent Abandonment Change of Plans Recompletion **New Construction** Non-Routine Fracturing Plugging Back Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice Dispose Water Other Run 4 1/2" casing (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* * REVISED * Workover existing water injection well as follows: 1. RIH with 4 1/2" 11.6# J-55 casing and set at 3444'. Cement casing back to surface. 2. Selectively perforate the injection interval of 2600'- 3433'(OA). 3. RIH with Baker AD-1 packer on 2 3/8" (IPC) tubing and set at ± 100 ' above top perforation. 4. Inject through perforations within injection interval. Subject to LIKE APPROVAL BY STATE 14. I hereby certify that the foregoing is true and correct Randy Jackson Date August 7, 1996 Title District Engineer (This space for Federal of State office use) TOTELS ENGINEER Date 6/21/91 (ORIG. SGD.) ARMANDO A LOPET Approved by Conditions of approval, if any

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to