

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-031844

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Fren Oil Company

9. WELL NO.

9

10. FIELD AND POOL, OR WILDCAT

Grayburg Jackson (OGSA)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

19-17S-31E

12. COUNTY OR PARISH 13. STATE

Eddy

N.M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Atlantic Richfield Company

3. ADDRESS OF OPERATOR

P. O. Box 1710, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

2310' FSL & 330' FEL (Unit letter I)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3611' DF

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

Plug & Abandon

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3445', PBD 3130'. Presently completed OH 2947-3130'. This well last produced 100% wtr & was shut in on 9/15/75. There are no other zones to recomplete this well in as the well is no longer needed for secondary recovery.

8-5/8" OD 24# csg set @ 506', cmtd w/50 sx.

7" OD 20# csg set @ 2592', cmtd w/130 sx.

5 1/2" OD 15.5# csg set @ 2948', cmtd w/125 sx (up into 7" OD csg)

Propose to P&A in the following manner:

1. Rig up, kill well, install BOP. POH w/completion assy.

2. RIH w/5 1/2" cmt retr on 2-3/8" OD tbq, set cmt retr @ 2850'.

3. Squeeze cmt thru retr w/100 sx Cl C cmt. Pull out of retr & spot 5 sx on top. Spot heavy gelled mud between plugs.

4. Run free point. Cut 5 1/2" OD csg from free point estimated @ 1300' & pull.

5. Spot 25 sx Cl C cmt (100' cmt plug) across 5 1/2" csg stub.

6. Perforate 7" csg w/4 holes @ 600'. Install swage on top of 7" csg & displace 135 sx Cl C cmt. Leave top of cmt inside 7" csg @ 300' from surface.

7. Spot 10 sx Cl C cmt @ surface. Erect regulation dry hole marker, clean & level location per BLM stipulations.

RECEIVED
JUL 29 1976
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Dist. Drlg. Supv.

DATE 7/29/76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side