

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

MAR 19 1996

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Marbob Energy Corporation

3. Address and Telephone No.

P. O. Drawer 217

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Sec.19 T-17-S R-31-E 990' FSL & 355' FEL Unit P

5. Lease Designation and Serial No.

LC-031844

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Fren Oil Company #16

9. API Well No.

30-015-05262

10. Field and Pool, or Exploratory Area

Cedar Lake Abo

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☐ Other  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- 1) T.A. 6-4-80 (A) Spot cement from 6916' - 6750' (B) Spot cement from 1450' - 1350'
- 2) 3-1-80 Hole in casing @ 140', perforated casing @ top of cement 1410' Squeezed with 790 sxs cement, tested to 1000 psi, O.K. no leaks
- 3) Load hole with mud, Tagged cement top @ 1054'
- 4) Spot 40 sxs cement @ 1054'
- 5) SPot 25 sxs cement @ 475'
- 6) Spot 10 sxs cement from 60' to surface - set PA marker
- 7) Job completed 3-4-96

RECEIVED

APR 18 1996

OIL CON. DIV.

DIST. 2

Approved as to plugging of the well and  
liability under bond is retained until  
surface restoration is completed.

Post 4/15/96  
T.L. 2  
P.H.

14. I hereby certify that the foregoing is true and correct

Signed Sharon J. Shaw

Title District Secretary

Date 3/11/96

(This space for Federal or State office use)

Approved by Orig. Signed by Sharon J. Shaw

Title

PETROLEUM ENGINEER

Date 4/15/96