

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

RECEIVED

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

SOCORRO PETROLEUM COMPANY

3. Address and Telephone No.

20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

990' FNL & 2310' FEL, Section 19-T17S-R31E

5. Lease Designation and Serial No

LC-029395-A

6. If Indian, Allotment or Tribe Name

N/A

7. If Unit or CA, Agreement Designation

N/A

8. Well Name and No.

Turner "A" #25

9. API Well No.

30-015-05276

10. Field and Pool, or Exploratory Area

GRAYBURG-JACKSON

11. County or Parish, State

EDDY COUNTY, NM

12. **CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA**

TYPE OF SUBMISSION

☒ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☐ Other

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well is to be plugged and abandoned by spotting a 25 sx Class "C" cmt plug (approximately 130' in length) in the 7" production casing on top of existing CIBP @ 1817'. The 7" production casing will then be perforated at 1250' (approximately 50' below the base of the salt) and squeezed w/125 sx of Class "C" cement. The 7" will then be perforated at 550' (approximately 50' below the 8 5/8" surface casing shoe) and squeezed with 200 sacks of Class "C" cement. All casing and annulus will be filled with cement. All casings will be cut off 4' below ground level and the appropriate dry hole marker installed.

This plug and abandonment has been verbally approved by the BLM's Shannon Shaw.

14. I hereby certify that the foregoing is true and correct

Signed

Jo Ann Hooks

JO ANN HOOKS
Title **ENGINEERING TECHNICIAN**

Date **August 3, 1994**

(This space for Federal or State office use)

Approved by **(ORIG. SGD.) JOE G. LARA**

Title

PETROLEUM ENGINEER

Conditions of approval, if any: *See attached.*

Date **8/26/94**

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See instruction on Reverse Side