

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYIN. M. O. C. C. COPY
SUBMIT IN T
(Other instruc.
verse side)ICATE*
on re-Form approved.
Budget Bureau No. 42-R142

5. LEASE DESIGNATION AND SERIAL NO.

LC 029395 (b)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Turner "B"

9. WELL NO.

11

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 20, T17S, R31E

1. OIL ☐ GAS ☐ OTHER ☒ Water Injection Well

2. NAME OF OPERATOR

Atlantic Richfield Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FNL, 660' FEL (Unit Letter H)

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3710' Grd.

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☒REPAIR WELL ☐(Other) Run 4½" Innerstring ☒PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

To effect a more efficient injected water pattern, we propose the following work.

1. Clean out to original T.D. and run 4½" OD 8R 9.5# new casing to T.D. Cement w/200 sx of Class "C" cement.
2. Perforate Jackson zone w/one 0.42" jet @ 3378, 3383, 3387, 3391, 3393, 3396, 3399, 3404, 3406, 3415, 3421, 3426, 3427, 3437, 3444, 3445, 3454, 3456, 3460, 3474, 3476, 3478, 3482, 3484, 3490, 3492 and 3494' (27 holes, GR-N log).
3. Treat w/3500 gallons 15% HCl acid and ball sealers.
4. Run tension packer on 2-3/8" tubing and set @ 3325' Load annulus w/treated fresh water and resume water injection.

Work to start about 1/20/70.

RECEIVED

DEC 16 1969

RECEIVED

DEC 15 1969

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. D. Dethlefs

TITLE

Dist. Drlg. Supervisor

DATE

12-12-69

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side