



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.  
Form Approved.Land Office Las CrucesLease No. 00935(b)Unit Turner "B"

RECEIVED

NOV 9 1962

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	X
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL	Subsequent Report of Perforation, Acidizing & Frac	X

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Well No. 43 is located 440 ft. from S line and 540 ft. from W line of sec 30  
24 1/4 Sec 20 175 18E 104N  
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
Grayburg Jackson Edley New Mexico  
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

- 2-14-62 WALTER Grayburg moved in NOU. Pulled rods & thg. Cleaned out w/ mud pump. Jet perforated 3000-3210 w/20 1/2" holes. Ran 2" thg/packer to 3150. Had acid washed perfor 3000-3210 w/100 gals. Ran Frac 3000, Min Frac 3000, inj rate 2 BPM. Frased with 2/30 lbs walnut hulls per gallon oil - screened out after 2500 gals oil in formation. 6000 pressure. Pulled thg & packer. Reperforated 3000-3210 w/20 1/2" jet shots. Ran 2" thg & packer to 3150. Had acid washed perfor 3000-3210 w/100 gals. Ran Frac 3000, Min Frac 3000, inj rate 5 BPM. Attempted to sandblast from w/ 10000 gals oil & 10000 lbs sand-sanded out w/ 2500 gals oil & 2500 lbs sand. Ran Frac 6000. Pulled thg & packer.
- 2-26-62 Ran 2" thg to 3000' to test.
- 4-6-62 WALTER Grayburg On 24 hr potential test a well pumped 8 bbls new oil & no water in 24 hrs from oil perforations 3000-3070 & new perforations 3000-3210. Final Report.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company Simclair Oil & Gas CompanyAddress 580 E BroadwayEdley, N.M.By ER WoodTitle Asst. Dist. Engr.Origination: WGS; on HFD, JM, File