Form 3160-5 (JUNE 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135

SUNDRY NOTICES AND REPORTS ON WELLS

Expires March 31, 1993

5. Lease Designation and Serial No.

SUNDRY NOTICES AND REPORTS ON WELLS				
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT -" for such proposals			6. If Indian, Allotte or Tribe Name	
SUBMIT IN TRIPLICATE			7. If Unit or CA, Agreement Designation	
1. Type of Well Oil Well Gas Well Other X Water Injection			Skelly Unit	
2. Name of Operator			8. Well Name and No.	
The Wiser Oil Company			62	
3. Address and Telephone No.			9. Well API No. 30-015-05316	
8115 Preston Road, Suite 400, Dallas, TX 75225 (214)265 080 4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			10. Field and Pool, or Exploratory Area	
4. Location of Well (Footage, Sec., 1., R., M., or Survey Description)			Grayburg Jackson 7-Rivers-QN-GB-SA	
Unit D, 660' FNL & 660' FWL, Sec 21, T17S, R31E			Lea, New Mexico	
12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data				
			PE OF ACTION	
X Subsequent Re	port Rec	andonment completion gging Back sing Repair tering Casing	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off X Conversion to Injection Dispose Water	
			(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form)	
Describe Proposed or Completed Operations (Cl subsurface locations and measured and true vertical)			of starting any proposed work. If well is directionally drilled, give	
06/23/97 MIRU DA&S W	3/97 MIRU DA&S WS # 321. ND WH. NU BOP. RIH w/7" Howco R-4 pkr. on 63 jts. 2-3/8" tbg.			
06/24/97 RIH w/pkr. to 2800'. Set pkr & attempted to test csg. w/no success. POH w/R-4 pkr. RIH w/7" Baker RBP on 2-3/8" tbg. Set RBP @ 2800'. Tstd csg to 500#. Held ok. POH w/RBP. RIH w/6-¼" bit on 2-3/8" tbg. Tagged fill @ 2941'. Pld to 2800'.				
• -	06/27/97 RIH w/tbg. Tagged sand @ 3062'. CO sand f/3062'-3235'. POH & LD 2-3/8" tbg. RIH w/7" Baker J-Lok pkr, on-off tool & 89 jts. 2-3/8" IPC tbg. to 2796.14'. ND BOP. Installed WH.			
06/30/97 Pmpd pkr fl dwr ATP 1981# @ 5	ATR 1081# @ 5 1 hom MTR 2412# @ 5 5 hom ISIR 1610# 5 min 1584# 10 min 1575# 15 min 1567# RDMO			
07/03/97 Initial injection	rate 400 BWPD @ 0#.		PM 73 97 WX	
14. I hereby certify that the foregoing is true and co	rrect		J.C.	
Signed: Sittly &	Title Proc	luction Administrator	Date 01/16/98	
(THIS SPACE FOR FEDERAL OR STATE OFFICE USE				
Approved By:	Title		Date	
Conditions of approval, if any:				