Form Approved.

0+5 MMS-Roswell, 1-File, 1-Engr. PWS, 1-Foreman EF, 1-BW, 1-JA, 1-Laura Richardson Midlan

	Form 9–331	Form Approved. Budget Bureau No. 42-R1424
	Dec. 1973 UNITED STATES	5. LEASE
	DEPARTMENT OF THE INTERIOR	
	· · · · · · · · · · · · · · · · · · ·	LC-029420 (b)
	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	THE REPORTS ON WELLS	7. UNIT AGREEMENT NAME
	SUNDRY NOTICES AND REPORTS ON WELLS	Dr_
(	(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	Skelly Unit ASCEVED  8. FARM OR LEASE NAME
-	ESE VOIT, USE TO THE GOLD TO T	Skelly Unit
	1. oil gas other Injection well	<del></del>
	Well Well	9. WELL NO. 18 1983
	2. NAME OF OPERATOR	10. FIELD OR WILDCATANAME C. D.
-	Getty Oil Company V  3. ADDRESS OF OPERATOR	Grayburg Jackson OFFICE
		11. SEC., T., R., M., OR BLK. AND SURVEY OR
-	P.O. Box 730, Hobbs, NM 88240  4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
	below.)	Sec. 21, T-17S, R-31E
	AT SURFACE: Unit Ltr. F, 1980' FNL & 1980' FWL	12. COUNTY OR PARISH 13. STATE
	AT TOP PROD. INTERVAL:	Eddy
	AT TOTAL DEPTH:	14. API NO.
	16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
	REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
		3767' DF
/	REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
	TEST WATER SHUT-OFF [	
	FRACTURE TREAT  SHOOT OR ACIDIZE	
	REPAIR WELL	(NOTE: Report results of multiple completion or zone
	PULL OR ALTER CASING	change on Form 9-330.)
	MULTIPLE COMPLETE	
	CHANGE ZONES	
	ABANDON*	
	(other)	
	17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertined	lirectionally drilled, give subsurface locations and
9/7/82	Rig up Xpert. 7" @ 2907'. TD 3585'. Pull pkr ran B. plug set @ 2839'.	1 90 jts 2 3/8" tbg, Howco R-4 tension
9/8/82		Pull plug & packer. Ran 90 jts 2 3/8
3, 0, 02	2818'. Baker AD-1 packer set @ 2822'. Dic	
9/9/82		
-, -, -	Displace hole w/ treated water. Start inje	
9/10/82	Pull thg & pkr. Ran thg w/ bull plug. Tes	st to 5000#. Pull bull plug ran tbg
	& pkr. Pkr did not hold.	
9/11/82	Ran Baker AD-1 packer 90 jts 2 3/8" (2817')	). Set packer @ 2929'. Start
	injection at 1:00 P.M.	
9/13/82	Rig down. Placed will back on injection.	
	Subsurface Safety Valve: Manu. and Type	Set @ Ft.
	18. I hereby certify that the foregoing is true and correct	
		tandantes Captambar 14 1982
SIGNED D. R. Crockett TITLE Area Superintendent September 14, 19		
(This space for Federal or State office use)		
ì	5005	SEP 1 F 1982
ĭ	$\Lambda \Lambda I$	<b>3</b> E!