

NM OIL CONS. COMMISSION  
Drawer DD  
Artesia, NM 88210

C/SF

Form 9-331  
Dec. 1973

O+5 - USGS - P.O. Box 1857  
Roswell, NM 88201

1 - Engr. - PS  
1 - Foreman - EF, LG

1 - File 1-Laura Richardso  
Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other

2. NAME OF OPERATOR

Getty Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 730 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1980  
AT SURFACE: 1980 FSL & 1900 FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Run 5 1/2" liner

5. LEASE  
LC-029420-B

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME RECEIVED  
Skelly Unit

8. FARM OR LEASE NAME

OCT 22 1982

9. WELL NO.  
13

10. FIELD OR WILDCAT NAME OFFICE  
Fren 7-Rivers

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 21, T17S, R31E

12. COUNTY OR PARISH Eddy  
13. STATE NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3812' DF

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1. Rig up pulling unit.
2. Install BOP.
3. Pull rods and tubing.
4. RIH with slotted liner, formation packer collar and 5 1/2" liner to top.
5. Cement 5 1/2" liner to surface.
6. Drill out 5 1/2" liner and formation packer collar.
7. Acidize slotted liner section 2115-2200'.
8. Swab back load.
9. Place well back on production.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dale R. Crockett

TITLE Area Superintendent DATE October 15, 1982

ACCEPTED FOR RECORD

space for Federal or State office use)

(ORIG. SGD.) DAVID R. GLASS

APPROVED BY  
CONDITIONS OF

APPROVAL IF ANY:

OCT 20 1982

U.S. GEOLOGICAL SURVEY

ROSWELL, NEW MEXICO

See Instructions on Reverse Side

RECEIVED

OCT 18 1982