

(SUBMIT IN TRIPLICATE)

Land Office Las Cruces
Lease No. 029420-b
Unit Dow "B"

APPROVED
MAR 26 1962
Sec. 21
ACTING DISTRICT ENGINEER

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

MAR 27 1962

| | | | |
|---|-------------------------------------|---|--|
| NOTICE OF INTENTION TO DRILL..... | | SUBSEQUENT REPORT OF WATER SHUT-OFF..... | |
| NOTICE OF INTENTION TO CHANGE PLANS..... | <input checked="" type="checkbox"/> | SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING..... | |
| NOTICE OF INTENTION TO TEST WATER SHUT-OFF..... | | SUBSEQUENT REPORT OF ALTERING CASING..... | |
| NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL..... | | SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR..... | |
| NOTICE OF INTENTION TO SHOOT OR ACIDIZE..... | | SUBSEQUENT REPORT OF ABANDONMENT..... | |
| NOTICE OF INTENTION TO PULL OR ALTER CASING..... | | SUPPLEMENTARY WELL HISTORY..... | |
| NOTICE OF INTENTION TO ABANDON WELL..... | | | |

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Hobbs, New Mexico - March 22, 1962

Dow "B"

Well No. 39 is located 2080 ft. from [N] line and 1980 ft. from [E] line of sec. 21

3 1/4 NE 1/4 Sec. 21
(1/4 Sec. and Sec. No.)

17-S
(Twp.)

11-E
(Range)

N.M.P.M.
(Meridian)

Wildest
(Field)

Eddy
(County or Subdivision)

New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We have an approved "Intention To Drill" on this well dated March 2, 1962, to drill to the San Andres Formation. We now propose to change our plans and drill with rotary tools from surface to total depth of approx. 5000' and test the Glorieta Formation. Casing program as follows:

| Size Hole | Size Casing | Casing Point | Sacks Cement |
|-----------|-------------|--------------|--------------|
| 12-1/4" | 9-5/8" | 610' | 400 |
| 7-7/8" | 5-1/2" | 5000' | 480 |

The pump & plug process will be used in cementing both strings of casing. The well will be perforated and treated with approx. 10,000 gals. lease oil & approx. 10,000# sand.

RECEIVED

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

MAR 28 1962

Company Skelly Oil Company

Address P.O. Box 38

Hobbs, New Mexico

By (ORIGINAL) H. E. Ash
(SIGNED)

Dist. Supt.

Title _____