Form 3160-5 (JUNE 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135

Expires March 31, 1993

BOILE TO OF LEGISLATION OF THE STATE OF			5. Lease Designation and Serial No.
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT -" for such proposals			6. If Indian, Allotte or Tribe Name
SUBMIT IN TRIPLICATE			7. If Unit or CA, Agreement Designation
Type of Well Oil Well			Skelly Unit
2. Name of Operator			8. Well Name and No.
The Wiser Oil Company			9. Well API No.
3. Address and Telephone No.			30-015-05353
8115 Preston Road, Suite 400, Dallas, TX 75225 (214)265-0080			10. Field and Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			Grayburg Jackson 7-Rivers-QN-GB-SA
11-10 660' FSI & 1980' FFI Sec 22 T17S R31E			11. County or Parish, State Fody
5 -, -		JUL 18 1997	Leg New Mexico
12.	Check Appropriate Box to Indicate	Nature of Notice, Report, or Other Data	THE OF ACTION
ТҮРЕ	OF SUBMISSION		YPE OF ACTION
	Notice of Intent	Abandonment	Change of Plans New Construction
X Subsequent Report		Recompletion Plugging Back	Non-Routine Fracturing
	Subsequent report	Casing Repair	Water Shut-Off
Γ	Final Abandonment Notice	Altering Casing	X Conversion to Injection
<u></u>	1 mai Abandomiene Potte	Other	Dispose Water
			(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form).
Describe Proposed or Consubsurface locations and	measured and true vertical depths for all man	rkers and zones pertinent to this zone?	ite of starting any proposed work. If well is directionally drilled, give
02/19/97	MIRU DA&S WS, LD 143 rods & pmp. Removed old WH, Installed new WH, Tagged btm. POH, Btm, @3668'.		
02/20/97	RIII w/Howco R-4 pkr on 2-3/8" thg. Set pkr @ 3200'. Attempted to tst esg. press to 450#. Bled to 0#. Pmpd 20 bbls hot wtr dn tbg. Drpd standing valve. Tstd tbg to 2000#. Pld standing valve. Reset pkr. Attempted to tst esg. Did not hold. POH w/pkr to run RBP. Changed procedure. RIII w/2-3/8" tbg. POH. LD 2-3/8" tbg. Removed BOP & RD unit. Prep to dig out WH.		
03/04/97	RIH w/bit & tagged cmt @3673'. POH & LD 2-3/8" tbg. RIH w/5-1-2" Baker J-Lok pkr & 101 jts 2-3/8" IPC tbg. ND BOP. Installed WH. HES pmpd 70 bbls pkr fl dn esg. Set pkr @ 3196'. Tstd esg to 500# for 30 min. Held OK. HES acidized perfs 3262'-3566' & open hole zone 3618'-3673' w/7500 gals 15% Fer-check acid & 2000# rock salt. Flushed w/90 bbls FW. ATP 2350# @4.8 bpm. MTP 2810# @ 5.1 bpm. ISIP 1856#. 5 min 1856#. 10 min 1828#. 15 min 1808#. RD HES.		
03/05/97 03/06-07/97	Installed injection valve. WO injection line.		Post ID-3 8-1-97 Prod to WIK
03/08/97	Initial injection rate 225 BWPD @ 1400#.		
4. Thereby certify that the fo			

Title

07/07/97

(THIS SPACE FOR FEDERAL OR STATE OFFICE USE)

Conditions of approval, if any:

Approved By: