

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instruction in Rules and Regulations of the Commission.

Hobbs, New Mexico January 22, 1941

Place

Date

OIL CONSERVATION COMMISSION.
Santa Fe, New Mexico.

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as _____

Skelly Oil Company Lynch "A" Well No. 2 in SW NW

Company or Operator

Lease

of Sec. 22, T. 17, R. 31, N. M. P. M., Maljamar Field, Eddy County

N.

The well is 1980 feet ~~XX~~ (S.) of the North line and 660 feet

(E.) (W₂) of the _____ line of section 22

(Give location from section or other legal subdivision lines. Cross out wrong directions)

If state land the oil and gas lease is No. _____ Assignment No. _____

If patented land the owner is _____

Address _____

If government land the permittee is B.V. Lynch Gov. Permit #029419a

Address _____

The lessee is _____

Address _____

We propose to drill well with drilling equipment as follows: _____

Cable tools top to total depth. Contractor-Sahara Drilg. Co., Monahans, Texas.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: _____

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
<u>10 1/2</u>	<u>8 5/8</u>	<u>32#</u>	<u>SH</u>	<u>650</u>	<u>Cemented</u>	<u>100</u>
<u>8"</u>	<u>7"</u>	<u>20#</u>	<u>New</u>	<u>3300</u>	<u>Cemented</u>	<u>200</u>

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil and gas sand should occur at a depth of about 3375 feet.

Additional information: In cementing the 8 5/8" OD casing the cement shall be circulated back to bottom of cellar. Halliburton process shall be used in cementing both strings.

Approved January 23, 19 41
except as follows:

Sincerely yours,

Kinky Skelly Oil Company

Company or Operator

By J. N. Dunevocy

Position District Supt.

Send communications regarding well to
Name Skelly Oil Company

Address Drawer D Hobbs, New Mexico

OIL CONSERVATION COMMISSION

By Roy Yarbrough

Title Oil & Gas Inspector