Form 3160-5 (November 1983) (Formerly 9-331)

UNITEL TATES DEPARTMENT OF THE INTERIOR

SUBMIT IN TRIPLICATE *
(Other Instructions on

Oil Cons. 6/5
Bulled Mur Di Vo Disto 25
130 Exters Grand Avenue

| BUREAU OF LAND MANAGEMENT reverse side) | | | | 5. LEASTERS ENANGMANT SET 140 NO. LC-029418-A | |
|--|---|-----------|------------------------------|--|------------------------|
| (Do not use this form | NOTICES AND REPORT for proposals to drill or to deepen or plug APPLICATION FOR PERMIT - " for suc | back to a | different reservoir. | 6. IF INDIAN, ALLOTTEE OR TRI | BE NAME |
| 1. | | | | 7. UNIT AGREEMENT NAME | |
| OIL GAS OTHER WIW | | | | Skelly Unit | |
| 2. NAME OF OPERATOR | | | | 8. WELL NO. | |
| The Wiser Oil Company | | | | 49 | |
| 3. ADDRESS OF OPERATOR P.O. Box 2568 Hobbs, New Mexico 88240 (505) 392-9797 | | | | 9. API Well No. 30-015-05359 | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) | | | | 10. FIELD AND POOL, OR WILDCAT Grayburg Jackson 7-Rivers-QN-GB-SA | |
| At surface | | | | 11. SEC., T., R., M., OR BLK. AND | |
| 1980' FNL & 1980' FEL Unit G | | | | SURVEY OR AREA Sec. 23-T17S-R31E | |
| 14. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.) | | | | 12. COUNTY OR PARISH | 13. STATE |
| | 3879' DF | | | Eddy County | NM_ |
| 16. Cł | heck Appropriate Box to indicate | e Nature | e of Notice, Report, or Othe | r Data | |
| NOTICE OF INTENTION TO: | | | | BSEQUENT REPORT OF: | |
| TEST WATER SHUT OFF | PULL OR ALTER CASING | \Box | WATER SHUT-OFF | REPAIRING WELL | |
| FRACTURE TREAT | MULTIPLE COMPLETE | | FRACTURE TREATMENT | ALTERING CASING | ; - |
| SHOOT OR ACIDIZE | ABANDON* | | SHOOTING OR ACIDIZING | ABANDONMENT* | |
| REPAIR WELL CHANGE PLANS (Other)(Note: Report results of | | | | f multiple completion on Well | |
| (Other) Completion or Recompletion Report and Log form.) | | | | | |
| | MPLETED OPERATIONS: (Clearly state ionally drilled, give subsurface locations a | | | | |
| Wiser requests approval to plug and abandon the well by the procedure listed below. | | | | 1 3 L 3 L 3 L 3 L 3 L 3 L 3 L 3 L 3 L 3 | N. 14. N. 14. O. |
| Surface Casing: 8-5/8" set @ 694' Production Casing: 7" @ 3255' Liner: 4-1/2" @ 3693' | | | | | |
| Perforations: 3320'-3596' | | | | y f s ≜ | |
| 1. TOH w/tbg, TIH w/CIBP & set @ 3300'. Cap w/50' cement. | | | | 3 - 35 0 15 13 - 35 0 15 0 15 13 - 35 0 15 0 15 0 15 0 15 0 15 0 15 0 15 0 | V. |
| 2. Tag cement & circulate abandonment mud. | | | | the section of the se | γ. (Δ |
| 3. TOH to 1600' & set 100' cement plug | g f/1500'-1600'. | | | en e | |
| 4. Tag cement plug @ 1500'. Perforate | 4-1/2" csg. @ 700' & circulate cement to surface. | Leave 100 | ' cement plug @ 600'-700'. | | |
| 5. Spot 50' cement plug to surràce. APPROVAL SUBJECT TO | | | | | |
| 6. Instair dry note marker. | | | | AL REQUIREMENTS AND | |
| 7. Clean location. SPECIAL STIPULATION | | | | | _ |
| | | | OI LOW | r our orknous VIIV | OLIED |
| 18. I hereby certify that the foregoing is | s true and correct. | | | | |
| signed M | TITLE Supe | rintend | lent | DATE October 19, 200 | 1 |
| (This space for Federal or State office APPROVED BY ORIG. SGD.) | e use) ALEXIS C. SWOBODA | PETR | OLEUM ENGINEER | NOV 07 21 |) <u>0</u> 1 |
| CONDITIONS OF APPROVAL F | TANY) | | | DATE | <u></u> |

*See Instruction On Reverse Side