


N. M. O. C. C. COPY  
(SUBMIT IN TRIPLICATE)

Budget Bureau No. 42-R358.4.  
Approval expires 12-31-60.



UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Land Office **Las Cruces**  
Lease No. **029418-3**  
Unit **Lea "B"**

RECEIVED

MAR 27 1962

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....	<b>Run Liner, Perforate &amp; Fracture</b>	<b>XX</b>

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

**Hobbs, New Mexico - March 23, 1962**

Lea "B"  
Well No. **1** is located **1980** ft. from **SW** line and **660** ft. from **E** line of sec. **23**  
**NE/4 SE/4 Sec. 23** **17-S** **31-E** **N.M.P.M.**  
(1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)  
**Grayburg Jackson** **Eddy** **New Mexico**  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is \_\_\_\_\_ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Run sand pump and cleaned out to T.D. 3880'. Set 4-1/2" OD liner from 3153' to 3876' with Baash-Ross Liner Hanger & cemented with 265 sacks. Plug down at 5:00 PM, February 22, 1962. WOC 48 hrs. Drilled and cleaned out cement to 3674'. F.B.T.D. 3674'.

Perforated 4-1/2" OD casing liner with 4 shots per ft. 3764-70', 3780-88', 3800-06', 3824-28', 3840-42' & 3852-66' - 40' - 160 holes. Treated through 4-1/2" OD liner perfs. 3764-3866' (intervals) with 2000 gals. 15% Reg. Acid, 42,092 gals. of lease oil, 40,000# 20/40 sand, & 200 ball sealers by Dowell, Inc. After recovering all lease oil well pumped 5 1/2 bbls. oil and 3 bbls. water in 24 hours.

Date work performed - February 15 thru March 1, 1962.

Date Potential - March 22, 1962.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **Skelly Oil Company**

Address **P.O. Box 38**

**Hobbs, New Mexico**

(ORIGINAL SIGNED) **H. E. Ash**

By \_\_\_\_\_

Title **Dist. Supt.**