

SF/ file

O+5 - USGS - P.O. Box 1857
 Roswell, NM 88201
 Form 9-331 1- NMOCD-Artesia
 1973

1 - Admin Unit
 1 - Midland
 1 - Engr. - PS
 1 - Foreman

1 - Foreman - LG
 1 - BB
 1 - BW

Form Approved.
 Budget Bureau No. 42-R1424

UNITED STATES
 DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

JUN 1 1982

2. NAME OF OPERATOR
 Getty Oil Company

O. C. D.
 ARTESIA, OFFICE

3. ADDRESS OF OPERATOR
 P.O. Box 730 Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980 FSL & 1980 FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
 FRACTURE TREAT ☐
 SHOOT OR ACIDIZE ☐
 REPAIR WELL ☐
 PULL OR ALTER CASING ☐
 MULTIPLE COMPLETE ☐
 CHANGE ZONES ☐
 ABANDON* ☐
 (other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐
☒

RECEIVED
 MAY 24 1982

OIL & GAS
 U.S. GEOLOGICAL SURVEY
 ROSWELL, NEW MEXICO

NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/18/82 Ran 3 15/16" mill. Milled on bad csg. 64-79'. Ran 3 13/16 shoe. Milled on bridge plug 1699-1700' pull mill.
 4/19/82 Ran 3 31/16" kutrite mill 8" extension mill to 1700-02'.
 4/20/82 Pull mill & ran retrieving tool. Could not move bridge plug. Pull tool, ran 3 13/16" shoe. Re-mill 1701-02'. Pull mill.
 4/21/82 Ran 3 15/16" kutrite shoe. Mill from 1700-2'. Pulled mill. Ran new mill & milled from 1701-1703'. Pull mill & retrieve bridge plug. Ran 3 7/8" bit & drill cmt. 1703-13'.
 4/22/82 Drld. cmt 1713-1794'. Pull bit. Ran blade bit & drilled cement 2035'. Fell to 2168'. Drilled stringers to 2323'.
 4/23/82 Drld. cmt stringer 2323-2558'. Well started flowing back. Ran bit to 3234'. Pull bit & ran Baker cmt. retainer & set at 3208'. Perfs 3243-3800'

(Cont'd on back)

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Dale R. Crockett TITLE Area Superintendent DATE May-13, 1982

(This space for Federal or State office use)

APPROVED BY _____
 CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____