

(SUBMIT IN TRIPLICATE)

Land Office **New Mexico**  
Lease No. **LC 029020-0**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYUnit \_\_\_\_\_  
**RECEIVED**

JUL 2 1964

**SUNDRY NOTICES AND REPORTS ON WELLS**

E. L. C.

ARTESIA, OFFICE

NOTICE OF INTENTION TO DRILL	SUBSEQUENT REPORT OF WATER SHUT-OFF
NOTICE OF INTENTION TO CHANGE PLANS	SUBSEQUENT REPORT OF <del>ABANDONMENT</del> ACIDIZING <b>&amp; perf</b>
NOTICE OF INTENTION TO TEST WATER SHUT-OFF	SUBSEQUENT REPORT OF ALTERING CASING
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	SUBSEQUENT REPORT OF ABANDONMENT
NOTICE OF INTENTION TO PULL OR ALTER CASING	SUPPLEMENTARY WELL HISTORY
NOTICE OF INTENTION TO ABANDON WELL	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

6/18, 19 <sup>64</sup>Well No. **2-6** is located **2310** ft. from **N** line and **2310** ft. from **W** line of sec. **22****NE/4 SW/4 Sec. 22**

(1/4 Sec. and Sec. No.)

**17-S**

(Twp.)

**30-E**

(Range)

**NMPM**

(Meridian)

**Jackson Abo**

(Field)

**Rddy**

(County or Subdivision)

**New Mexico**

(State or Territory)

The elevation of the derrick floor above sea level is **3662** ft. **KB****DETAILS OF WORK**

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

2/18/64 - Well died.

3/10/64 - Pulled tbg., FGAC set Baker bridge plug # 6920, w/bailer placed 3' cal-seal plug, FBTD 6915 (old perf. 6924-32), FGAC perf. 6904-10 w/2 shts./ft., shut down w/ osg. pkr. set and treated Abo oil on back side.

3/11/64 - Treated new perfs. 6904-10 w/300 gal. HX acid max. treat press. 800#, probably communicated, sub. &amp; flowed 30 bbls. oil 12/64" in 18 hrs. 3/11 to 3/17/64 - Flowed approx. 80 BOPD for 3 days and died, too much water, fairly sure communicated w/ lower (old perf gone.) Shut in.

3/23/64 - Pld. tbg., Welox set cal-seal &amp; free sd. plug, top 6877, shut dn.

3/24/64 - Tag top plug #6910, plug dropped during night, pumped into fa. thru perfs. 6904-10, prep sqz. Halliburton RTTS sqz. pkr. sqzd 60 ex Incer, hold w/4000#, shut down. 3/25/64 - Press up 4000# hold-Welox perf. 6877-82 from FBTD 6896 w/2 shts/ft. A/300 gal HX, max. treat 3100# flowed 57 bbls oil on 9/64" ok. on

15/64" 10 BOPD for 4 hrs., out back to 12/64". Well died 3/3, sub. back and flowed to 5/10/64.

Company \_\_\_\_\_ Shut-in waiting on pumping unit-

Address \_\_\_\_\_ Halliburton pkr. still in hole.

COMPANY **Robert G. Hanagan**By **Hugh E. Hanagan**  
**Hugh E. Hanagan**

P. O. Box 1737, Roswell, New Mex.

Title \_\_\_\_\_