

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN T
(Other instructions
reverse side)ICATE*
on reForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-028992 J

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Grayburg-Jackson Unit

8. FARM OR LEASE NAME

Tract 5

9. WELL NO.

5-1

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson Unit

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASE SW Sec. 22 T-17S
R-30E

12. COUNTY OR PARISH

Eddy

13. STATE

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☐ OTHER

Water Injection

2. NAME OF OPERATOR

Ambassador Oil Corporation

3. ADDRESS OF OPERATOR

Fort Worth, Texas Local Box 260

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

C-SE 1/4 SW 1/4 Sec. 22, T-17-S, R-30-E

660/5 1920/W

14. PERMIT NO.

R-2323

15. ELEVATIONS (Show whether SF, RT, GR, etc.)

3625

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Intentions were to complete as water injection by cementing 4 1/2" 11.60# casing to surface and recover intermediate strings of casing. We were unable to shut off surface water with 8 5/8 casing. We cemented 496' of 8 5/8 24# casing with 50 sacks cement. W. O. C. 24 hrs. Drilled out under casing and tested--water shut off. Drilled to 3208', Top San Andres. Intentions are to complete with 4 1/2" 11.60# casing and cement above Frem(7-Rivers) Pay at 1925'. Abrasi Jet completion with perforations between 3165-3175', cased hole to 3208'.

RECEIVED

AUG 4 1965

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE July 19, 1965

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
AUG 4 1965
R. L. BENTLEY
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and state well site conditioned for final inspection looking to approval of the abandonment.