

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Sinclair Oil & Gas Company		8. FARM OR LEASE NAME Turner A	
3. ADDRESS OF OPERATOR P. O. Box 1920, Hobbs, New Mexico 88240		9. WELL NO. 36	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' from the East line and 1800' from the North line		10. FIELD AND POOL, OR WILDCAT Grayburg Jackson	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, OR, etc.)	
12. COUNTY OR PARISH Eddy		13. STATE New Mexico	

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐

(Other)

PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐

(Other)

REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

Spud, run surface csg., cement & test

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 11-18-67 Spud 12-1/4" hole at 1:30 PM on 11-18-67, and drilled surface and red bed to 605'.
- 11-19-67 Ran 9-5/8"OD 32.30# H₄₀ casing, set @ 605' and cemented with 350 sacks incor class C, 2% cal. chl. cement. Cement circulated to the surface. WOC 19-1/2 hrs.
- 11-20-67 Pressure tested surface casing to 800# for 30 min. Tested OK.

RECEIVED

DEC 6 1967

C. C. C.
ARTESIA, OFFICERECEIVED
DEC 4 1967
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICORECEIVED
NOV 29 1967
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE

11-28-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

DEC 11 1967

*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICOAPPROVED
DEC - 5 1967
R. L. ELLIEMAN
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

507-551

11-10-67 Pressure tested surface casing to 100' for 30 min.
11-12-67 Class C, 28 cal. GMI cement. Cement circulated to
top of hole. 32.304 H₂O casing, set 105' and
11-12-67 Spud 12-1/4" hole at 1:30 PM on 11-12-67, and
11-12-67

1960' from the East line and 1800' from the North line

A. O. Box 1920, Hobbs, New Mexico 88240

Standard Oil & Gas Company

STANDARD OIL AND GAS COMPANY

GEOLOGICAL SURVEY

DEPARTMENT OF THE INTERIOR
UNITED STATES