

clsf
gp

OIL CONSERVATION DIVISION

2040 Pacheco St.
Santa Fe, NM 87505

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.
30-015-2010 **20110**

Indicate Type of Lease
STATE FEE

State Oil & Gas Lease No.
B-2023

Lease Name or Unit Agreement Name
G-J West Coop Unit

Well No.
57

Pool name or Wildcat
Grbg Jackson SR Q Grbg SA

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)


Type of Well:
OIL WELL GAS WELL OTHER

Name of Operator
Mack Energy Corporation

Address of Operator
P.O. Box 960 Artesia, NM 88211-0960

Well Location
Unit Letter K : 1980 Feet From The South Line and 1980 Feet From The west Line
Section 16 Township 17S Range 29E NMPM Eddy County

Elevation (Show whether DF, RKB, RT, GR, etc.)
3587RKB



11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ANBANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>		CASING TEST AND CEMENT JOB <input type="checkbox"/>	
OTHER: <input type="checkbox"/>		OTHER: <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Notify OCD 24 hrs. Before starting

1. POH w/ rods & tubing
2. RIH open end to 2200 spot 100' plug from 2100 to 2200 woc & tag
3. Spot 100' plug from 975 to 1075' (salt 1025) Perforate 4 1/2" csg @ 1075'. Squeeze 100' cement Plug, Inside + Outside 4 1/2" csg. TAG
4. Perf @ 446' sqz 100' plug from 446' to 336' (8 5/8 shoe 396) Perforate 4 1/2" csg @ 446'. Squeeze 100' cement Plug, Inside + Outside 4 1/2" csg. TAG
5. Circulate cmt from 30' to surface Perforate 4 1/2" csg @ 60'. Circulate cmt to surface. Inside + Outside 4 1/2" csg.
6. Cut off well head install dry hole marker

* Beine gel between cement Plugs.
Notific N.M.O.C.D. to witness Plugging Operations.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Wayne Brooks TITLE Agent DATE 03-23-01

TYPE OR PRINT NAME Wayne Brooks TELEPHONE NO. (915)580-7161

APPROVED BY Mike Stullfeld TITLE Field Rep. II DATE 3/23/2001

CONDITIONS OF APPROVAL, IF ANY:

(This space for State Use)