

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRI-CATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. 028731-3	
2. NAME OF OPERATOR Sunray DX Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME -	
3. ADDRESS OF OPERATOR P. O. Box 1416 - Roswell, New Mexico 88201		7. UNIT AGREEMENT NAME -	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FNL, 1980' FEL, Unit GNAME CHANGED TO: SUN OIL CO. - DX DIVISION OCTOBER 25, 1968		8. FARM OR LEASE NAME M. Dodd "B"	
14. PERMIT NO.		9. WELL NO. 29	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3592 GR		10. FIELD AND POOL, OR WILDCAT Grayburg Jackson	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 10, T-17-S, R-29-E	
		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☒	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- Moved in and rigged up rotary rig. Spudded 1:30 P.M. 9-14-68.
- Drilled 12-1/4" hole to 530'. Ran 17 jts, 8-5/8", 24#, J-55 casing to 526' CP. Cemented w/300 sxs Class "C" cement, 2% CaCl. Circ 20 sxs. PD 10:30 P.M. 9-14-68. WOC 18 hours. Tested casing to 1000 psig for 30 min. Test OK.
- Drilled 7-7/8" hole to 2700' TD. Ran Schlumberger Gamma Ray Density 2406 to surface. Ran 86 jts, 4-1/2", 9.5#, J-55 casing, CP at 2690'. Cemented with 250 sxs Incor Poz. PD 9:30 P.M. 9-18-68. Tested casing to 1000 psig for 30 min. Test OK. Top of cement at 1600' by temperature survey.

RECEIVED
OCT 8 1968
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED F. D. Lebo	TITLE District Engineer	DATE 10-3-68
--------------------------	--------------------------------	---------------------

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

*See Instructions on Reverse Side

APPROVED
OCT 7 - 1968
R. L. OLEMAN
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.