

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
FORM APPROVED
Drawer DD Budget Bureau No. 1004-0135
Artesia, NM 88210 Exp. Date December 30, 1990

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

SUBMIT IN TRIPLICATE

1. Type of Well

☐ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Marbob Energy Corporation

3. Address and Telephone No.

P.O. BOX 227, Artesia, NM 88210 (505) 748-3303

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FNL & 1980 FEL SEC 13 T-17-S R-29-E UNIT G

5. Lease Designation and Serial No.

LC 028784-C

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

NMNM88525X

8. Well Name and No.

Burch Keely Unit #14

9. API Well No.

30-015-20340

10. Field and Pool, or Exploratory Area

GRBG JACKSON SR Q

11. County or Parish, State

Eddy, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 1) 4½" CIBP set @ 2420' Cap with 35' cement 3-23-92
- 2) Load hole with mud
- 3) Perforate 4½" casing @ base of salt 958' Squeeze with 50 sacks cement W.O.C.
Tag cement top @ 840'
- 4) Perforate 4½" casing @ top of salt 508' Squeeze with 50 sacks cement W.O.C.
Tag cement top @ 393'
- 5) Perforate 4½" casing @ 60' Circulate cement to surface between 4½" & 8-5/8" & open hole
Set PA marker
- 6) Job completed 10-25-95

Approved as to plugging of the well bore
Liability under bond is retained until
surface restoration is completed.

14. I hereby certify that the foregoing is true and correct

Signed Educa H. Kleeb

Title District Secretary

Date 11-2-95

(This space for Federal or State office use)

C. g. Signed by Shannon J. Shaw

Approved by _____
Conditions of approval, if any: _____

Title PETROLEUM ENGINEER

Date 12/8/95