

RECEIVED
OIL CONS. COMMISSION
Drawer DD-20
Artesia, NM 88210

Form Approved.
Budget Bureau No. 42-R1424

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

JAN - 8 '90

2. NAME OF OPERATOR
Devon Energy Corporation

C. C. D.

3. ADDRESS OF OPERATOR
1500 Mid-America Tower, OKC, OC 73102

RESIA, OFFICE

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FNL & 1980' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

☐

FRACTURE TREAT ☐

☐

SHOOT OR ACIDIZE ☐

☐

REPAIR WELL ☐

☒

PULL OR ALTER CASING ☐

☐

MULTIPLE COMPLETE ☐

☐

CHANGE ZONES ☐

☐

ABANDON* ☐

☐

(other) ☐

☐

5. LEASE

NM 2933

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Etz State Unit (TR 1) #2

8. FARM OR LEASE NAME

Collier Federal

9. WELL NO.

2

10. FIELD OR WILDCAT NAME

Grayburg

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

17-17S-30E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

14. API NO.

30-015-20598

15. ELEVATIONS (SHOW DF, KDB, AND WD)

GL 3673'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11-01-89 Moved in and rigged up Clarke Well Srv. Pulled pump, rods and tbg. Nippled up blow out preventer. Ran 4 1/2" csg scraper 2810'. Trpd csg scraper. Rigged up Jarrell Wireline. Set 4 1/2" Alpha cast iron bridge plug 2797' w/1/2 sx cement on top. SDON.

11-02-89 Ran tbg. Tagged 2788'. Nippled down blow out preventer. Ran pump and rods. Rigged down and released Clarke Well Srv. Hung well on. Ran production string as listed on reverse.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct.

SIGNED Candi R. Graham TITLE Candi R. Graham

DATE 12-15-89

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____

DATE _____

CONDITIONS OF APPROVAL, IF ANY:

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 O - 347-166

Etz State Unit (TR 1) #2

mud anchor w/bull plug	30.45'
perf'd sub	4.0'
seating nipple at 2730.58' GL	1.10'
89 jts 2 3/8" 4.7# J55 EUE 8rd tbg	2695.03'
2" X 1 1/2" X 12' THD pump	
108-3/4" X 25' rods	
8', 6', 4', 2' X 3/4" pony rods	
polish rod w/liner 1 1/4" X 22'	