

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPL
(Other instructions
reverse side)TE-
re-Form approved.
Budget Bureau No. 42-R1474.

5. LEASE DESIGNATION AND SERIAL NO.

NM-074937

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Parke "F"

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Grayburg-Jackson SR-Q
G-SA11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10, T-17S, R-30E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

General American Oil Company of Texas ✓

3. ADDRESS OF OPERATOR

P. O. Box 128 Loco Hills, New Mexico 88255

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)

At surface

1980' FSL and 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3720' RT

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

A small workover pit was dug.

Tubing and rods were pulled.

Set bridge plug at 2016'.

Ran Acoustic Log.

Perforated at 1930' with 4 shots.

Squeezed with 100 sacks of Halliburton Class "H" cement.

Ran Temperature Survey — showed cement outside of 4-1/2" casing at 1590'.

Perforated — 1874' - 1889' with 2 shots per foot.

Acidized with 4,000 gallons of 15% N.E. acid.

Perforated — 1867' - 1880' with 4 shots per foot.

Fraced with 20,000# of 20/40 sand and 20,000 gallons of gelled water.

Returned well to production.

RECEIVED

NOV 28 1980

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED Rendell M. HawkinsTITLE Field SuperintendentDATE November 26, 1980

(This space for Federal or State office use)

APPROVED BY _____

CONDITIONS OF APPROVAL, IF ANY: _____

TITLE _____

ACCEPTED FOR RECORD
DATE _____

DEC 3 1980

U.S. GEOLOGICAL SURVEY

*See Instructions on Reverse Side